



#### Color Variants

**BX481111**  
Stainless steel-backed full glass door  
Width 76 cm

#### Included accessories

2 x enamel baking tray.  
suit. pyrolytic clean.  
1 x rotary spit.  
2 x grill shelf.  
2 x grill tub with grid.  
1 x pluggable meat probe.

#### Optional accessories

**BA018105**  
Pull-out system  
**BA028115**  
Baking tray, enamelled  
**BA038105**  
Wire rack, chromium-plated  
**BA058115**  
Heating element for baking stone and  
Gastronorm roaster  
**BA058133**  
Baking stone  
**BS020002**  
Pizza paddle, set of 2  
**GN340230**  
Gastronorm roaster in cast aluminium

#### Product Variants

**BX480111**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Controls centered

**BX481111**  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Controls centered

**Pyrolytic system**  
17 heating methods, with core  
temperature probe, rotisserie spit  
and baking stone function  
TFT touch display  
Electronic temperature control from  
30 °C to 300 °C  
2 x 110 litres net volume

#### Heating methods

Hot air. Eco hot air. Top + bottom heat.  
Top + 1/3 bottom heat. Top heat. 1/3  
top + bottom heat. Bottom heat. Hot  
air + bottom heat. Hot air + 1/3 bottom  
heat. Full surface grill + circulated air.  
Full surface grill. Compact grill. Baking  
stone function. Roaster function. Dough  
proofing. Defrosting. Keeping warm.

#### Handling

Rotary knob and TFT touch display  
operation.  
Information key with use indications.  
Side-opening door opens up to 180°  
angle.

#### Features

Core temperature probe with automatic  
shut off (lower oven).  
Rotisserie spit (lower oven).  
Baking stone socket.  
Actual temperature display.  
Rapid heating.  
Timer functions: cooking time, cooking  
time end, timer, stopwatch, long-term  
timer.  
60 W halogen light on the top.  
2x10 W halogen light on the side.  
Enamelled side shelf supports with 5  
tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with  
quadruple glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature  
protection.

#### Cleaning

Pyrolytic system.  
Gaggenau enamel.  
Heated air cleaning catalyser.

#### Planning notes

Door hinge not reversible.  
The door panel surface of the  
appliance extends 47 mm from the  
furniture cavity.  
The outer edge of the door handle  
extends 94 mm from the furniture  
cavity.  
Consider the overhang, incl. the door  
handle, when planning to open drawers  
next to the appliance.  
When planning a corner solution, pay  
attention to the 90° door opening  
angle.  
To achieve the 550 mm installation  
depth, the connection cable needs to  
follow the slanted edge on the lower  
right hand corner of the housing.  
The mains socket needs to be planned  
outside of the built-in niche.

#### Connection

Total connected load 9.2 KW.  
Plan a connection cable.

#### Characteristics

**Color / Material Front**  
Stainless steel  
**Construction type**  
Built-in  
**Integrated Cleaning system**  
**Dimensions of the product (mm)**  
1428 x 752 x 547  
**Dimensions of the packed product  
(HxWxD) (mm)**  
1765 x 755 x 840  
**Control Panel Material**  
Alu  
**Door Material**  
Glass  
**Net weight (kg)**  
160.910  
**Usable volume of cavity (l)**  
110  
**Cooking method**  
Baking stone function, Bottom heat,  
Conventional heat, Defrost, Dough  
proving setting, Full width grill, Half  
width grill, Hot Air, Hot Air-Eco, Hot air  
grilling, Roaster function, Top heat,  
warming  
**First cavity material**  
Enamelled  
**Oven control**  
electronic  
**Number of interior lights**  
2  
**Approval certificates**  
Australia Standards, CE, Ukraine, VDE  
**Length of electrical supply cord (cm)**  
**EAN code**  
4242006241896

#### Consumption and connection features

**Energy efficiency class (2010/30/EC)**  
A  
**Energy consumption per cycle  
conventional (2010/30/EC)**  
1.53  
**Energy consumption gas oven per cycle  
conventional (2010/30/EC)**  
**Energy consumption per cycle forced  
air convection (2010/30/EC)**  
0.96  
**Energy consumption gas oven per cycle  
forced air convection (2010/30/EC)**  
**Energy efficiency class (2010/30/EC) -  
cavity 2**  
A  
**Energy consumption per cycle  
conventional - cavity 2 (2010/30/EC)**  
1.53  
**Energy consumption gas oven per cycle  
conventional - cavity 2 - NEW (2010/30/  
EC)**  
**Energy consumption per cycle forced  
air convection - cavity 2 (2010/30/EC)**  
1.08  
**Energy consumption gas oven per  
cycle forced air convection - cavity 2  
(2010/30/EC)**  
**Energy efficiency index (2010/30/EC)**  
95.0  
**Energy efficiency index cavity 2  
(2010/30/EC)**  
106.9  
**Connection rating (W)**  
9200  
**Current (A)**  
**Voltage (V)**  
220-240  
**Frequency (Hz)**  
50  
**Plug type**  
fixed connection, no plug

created on 2020-07-02

Page 1

BX481111  
Double oven 400 series  
Stainless steel-backed full glass door  
Width 76 cm  
Controls centered  
created on 2020-07-02  
Page 2

