



CE291101
Frameless
Width 90 cm

Frameless for flush installation
Frying sensor function
Three-ring cooking zone up to 27 cm
Large roasting zone
Sensor control with direct selection of output level

Cooking zones

2 Super-Quick cooking zones ø 18 cm (1800 W); together they convert to 18 x 41.5 cm (4400 W) roasting zone.
1 Super-Quick cooking zone ø 12 cm (750 W), converts to ø 21 cm (2100 W, with booster 2600 W) cooking zone.
1 Super-Quick cooking zone ø 14.5 cm (1050 W), converts to ø 21 cm (2200 W) or ø 27 cm (3080 W) cooking zone.
1 Super-Quick cooking zone ø 14.5 cm (1200 W, with booster 1600 W).

Handling

Sensor control with direct selection of output level.
Cooking zone marking.
Electronic power control in Variable 17-stage power settings for each zone.

Features

Frying sensor function for ø 21 cm cooking zone.
Booster function.
Cooking timer for up to 99 minutes.
Short-term timer.
Options menu.

Safety

Main switch.
Operation indicator.
2 stage Hh residual heat indicator for each zone
Child lock.
Safety shut-off.

Planning notes

Immersion depth 51 mm, depth at plug socket 51 mm.
The cooktop must not be installed lower than the top edge of the worktop. Under the plug socket, a 10 mm clearance must be observed from side panels or from intermediate shelf.
The cooktop must be freely accessible from underneath to be able to detach the cooktop's base in a downward direction.
Installation possible in a 60 cm wide lower cabinet.
Appliance must be fixed from underneath.
Cooktop clamping range: 20 - 50 mm.
Joint width may vary due to dimensional tolerances of the glass ceramic cooktop and the worktop cut-out.
Appliance weight: approx. 13.

Connection

Total connected load 11.0 KW.
Plan a connection cable.

Characteristics

Product name/family
Cooking zone ceramic

Construction type
Built-in

Energy input
Electric

Total number of positions that can be used at the same time
5

Type of control setting devices
Min. required niche size for installation (HxWxD)

Width of the appliance
908

Dimensions
51 x 908 x 520

Dimensions of the packed product (HxWxD)
100 x 1120 x 620

Net weight
12.7

Gross weight
14.5

Residual heat indicator
Separate

Location of control panel
Hob front

Type of external control possibility

Basic surface material
Ceramic

Color of surface
Black

Color of frame

Length of electrical supply cord

EAN code
4242006265656

Electrical connection rating

Gas connection rating

Fuse protection
3*20

Voltage
220-240

Frequency
50

Consumption and connection features

created on 2023-03-14
Page 1

Color Variants

CE291101
Width 90 cm

Optional accessories

GP900003
Stainless steel frying sensor pan

