



<b>CG492211</b>
<b>400 series gas cooktop</b>
<b>Stainless steel</b>
<b>Width 100 cm</b>
<b>Natural gas 20 mbar</b>
<b>Wok burner with 6 KW</b>

Five multi-ring burners, up to 18 kW  
Full electronic power level regulation on 12 levels  
Precise and reproducible flame size  
Automatic fast ignition, electronic flame monitoring with automatic re-ignition  
Simmer function for cooking on a very low output level  
Solid smooth-surface cast pan supports on the same level as the worktop  
Solid stainless steel control knob

#### Cooking zones

1 multi-ring wok burner (300 W – 6000 W), suitable for pots up to max. ø 32 cm.  
2 two-ring high output burners (165 W – 4000 W), suitable for pots up to max. ø 28 cm.  
2 two-ring standard burners (165 W – 2000 W), suitable for pots up to max. ø 28 cm.

#### Handling

Control knobs with illuminated ring, cooking zone and output level markings.  
One-handed operation.  
Full electronic control in 12 output levels for exact power level adjustment plus simmer function.  
Automatic fast ignition.

#### Features

Simmer function.  
Three-part pan support with flat, continuous pot surface, on the same level as the worktop.  
Brass burner rings.

#### Safety

Electronic flame monitoring with automatic re-ignition.  
Residual heat indication.  
Safety shut-off.

#### Planning notes

The frame set (necessary installation accessory) can be sent in advance to the manufacturer of the stainless steel or granite worktop for fitting.  
Special nozzles can be ordered as spare parts.  
Plan for an electrical connection (the appliance is not operable without power supply).  
The horizontal positioning of the knobs may be aligned with the specific burners.  
The drawing "Installation of the control knob" must be observed if the panel is more than 23 mm thick (there must be a recess at the rear).  
Minimum worktop depth 70 cm.  
Air intake from above.  
No intermediate shelf required.  
Due to the separate frame welded into the worktop, all parts remain fully accessible.  
Rear panel and wall trims must be heat-resistant and consist of a non-flammable material.  
The appliance can be fixed from above.  
A minimum lateral clearance of at least 300 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted.

#### Characteristics

<b>Product name/family</b>
gas hob w integrated controls
<b>Construction type</b>
Built-in
<b>Energy input</b>
Gas
<b>Total number of positions that can be used at the same time</b>
5
<b>Type of control setting devices</b>
<b>Required niche size for installation (HxWxD)</b>
157 x 983-983 x 580-580
<b>Width of the appliance</b>
1002
<b>Dimensions</b>
157 x 1002 x 599
<b>Dimensions of the packed product (HxWxD)</b>
290 x 1010 x 700
<b>Net weight</b>
34.7
<b>Gross weight</b>
37.5
<b>Residual heat indicator</b>
Separate
<b>Location of control panel</b>
External control
<b>Type of external control possibility</b>
<b>Basic surface material</b>
brushed stainless steel
<b>Color of surface</b>
Stainless steel
<b>Color of frame</b>
Stainless steel
<b>Approval certificates</b>
CE, Eurasian, G-Mark, Ukraine, VDE
<b>Length of electrical supply cord</b>
140
<b>EAN code</b>
4242006262082
<b>Electrical connection rating</b>
15
<b>Gas connection rating</b>
18000
<b>Fuse protection</b>
<b>Voltage</b>
220-240
<b>Frequency</b>
60; 50

#### Consumption and connection features

created on 2022-08-02  
Page 1

With a total connected load of more than 11 kW local regulations concerning room ventilation, room size and combination of extraction or recirculation hoods must be observed.  
The minimum distance between the cooktop surface and a cabinet above, out of combustible material, needs to be 76 cm.  
The minimum distance to a ventilation above is shown at the planning hints for the individual ventilation product.  
The combination with VL 430/431 is not recommended, since the air extraction from the centre burner cannot be guaranteed due to the distance.  
Appliance weight: approx. 35.

#### Connection

Total connected load gas 18.0 KW.  
Total connected load electric 15.0 W.  
Connecting cable 1.4 m with plug.

#### Color Variants

**CG492211**  
**Stainless steel**  
**Width 100 cm**

#### Included accessories

1 x WOK attachment ring.

#### Optional accessories

**WP400001**  
**Wok pan made of multiple-layer material**

#### Installation Accessories

**CA429410**  
**Frame set including decorative frame (to be welded in) and holding frame**

