



CI261114

Optional accessories

Installation Accessories

Induction cooktop 200 series 60 cm

CI261114

- Sturdy stainless steel frame
- Oval roasting zone switches on automatically
- Sensor control with direct selection of output level
- 1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W), automatically switches to a 18 x 28 cm roasting zone (2000 W, with booster 3700 W).
- 1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
- Sturdy stainless steel frame
- Oval roasting zone switches on automatically
- Sensor control with direct selection of output level

Cooking zones

1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W), automatically switches to a 18 x 28 cm roasting zone (2000 W, with booster 3700 W).

1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).

1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W).

1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

Handling

Sensor control with direct selection of output level.

Cooking zone marking.

Electronic power control in 17 output levels.

Features

Booster function for each cooking zone.

Cooking timer for up to 99 minutes.

Short-term timer.

Options menu.

Power management.

Safety

Main switch.

Operation indicator.

Pot detection.

2 stage Hh residual heat indicator for each zone

Child lock.

Safety shut-off.

Planning notes

Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.

The wok pan WP 400 001 cannot be used with this appliance.

Appliance must be fixed from underneath.

Appliance weight: approx. 13.

Connection

Total connected load 7.4 KW.

Connecting cable 1.5 m without plug.

