



Color Variants
CI261114
Stainless steel frame
Width 60 cm

CI261114
200 series induction cooktop
Stainless steel frame
Width 60 cm

Sturdy stainless steel frame
Oval roasting zone switches on automatically
Sensor control with direct selection of output level

Cooking zones

1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W), automatically switches to a 18 x 28 cm roasting zone (2000 W, with booster 3700 W).
1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
1 induction cooking zone ø 18 cm (1800 W, with booster 3100 W).
1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

Handling

Sensor control with direct selection of output level.
Cooking zone marking.
Electronic power control in 17 output levels.

Features

Booster function for each cooking zone.
Cooking timer for up to 99 minutes.
Short-term timer.
Options menu.
Power management.

Safety

Main switch.
Operation indicator.
Pot detection.
2 stage Hh residual heat indicator for each zone
Child lock.
Safety shut-off.

Planning notes

Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.
The wok pan WP 400 001 cannot be used with this appliance.
Appliance must be fixed from underneath.
Appliance weight: approx. 14.

Connection

Total connected load 7.4 KW.
Connecting cable 1.5 m without plug.

Characteristics

Product name/family
Cooking zone ceramic

Construction type
Built-in

Energy input
Electric

Total number of positions that can be used at the same time
4

Type of control setting devices
Required niche size for installation (HxWxD)
55 x 560-560 x 490-490

Width of the appliance
590

Dimensions
55 x 590 x 520

Dimensions of the packed product (HxWxD)
130 x 750 x 600

Net weight
14.1

Gross weight
15.3

Residual heat indicator
Separate

Location of control panel
Hob front

Type of external control possibility
Basic surface material
Ceramic

Color of surface
Black, Stainless steel

Color of frame
Stainless steel

Approval certificates
AENOR, CE, G-Mark

Length of electrical supply cord
150

EAN code
4242006282202

Electrical connection rating
7400

Gas connection rating

Fuse protection

Voltage
220-240

Frequency
50; 60

Consumption and connection features

created on 2022-08-05
Page 1

