



CI262111
Flex induction cooktop 200 series
Stainless steel frame
Width 60 cm

Sturdy stainless steel frame
Flex function for combining the rectangular cooking areas
Free positioning of cookware inside combined cooking areas
Cooking sensor function for temperature control in pots
Frying sensor function for temperature control in pans
Twist-Pad control with removable magnetic knob
Easy control of all functions with two color displays

Color Variants

CI262111
Stainless steel frame
Width 60 cm

Optional accessories

CA060300
GP900001
Stainless steel frying sensor pan
GP900002
Stainless steel frying sensor pan
GP900003
Stainless steel frying sensor pan

Cooking zones

2 flex induction cooking areas 19x23 cm (2200 W, with booster 3700 W), linked together 38x23 cm (3300 W, with booster 3700 W).
 1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
 1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

Handling

Twist-Pad control with removable magnetic knob.
 User friendly control with two color display (white / orange).
 Cooking zone, and cooking area marking.
 Electronic power control in Variable 17-stage power settings for each zone.

Features

Flex function for rectangular cooking areas.
 Cooking sensor function (in use with cooking sensor CA 060 300).
 Frying sensor function.
 Booster function for pots.
 Booster function for pans.
 Keep warm function.
 Stopwatch.
 Cooking timer for up to 99 minutes.
 Short-term timer.
 Options menu.
 Power management.
 Cooktop-based ventilation control (with suitable hood).
 Integrated WiFi module for digital services (Home Connect).
 The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Main switch.
 Operation indicator.
 Pot detection.
 2 stage Hh residual heat indicator for each zone
 Child lock.
 Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. The wok pan WP 400 001 cannot be used with this appliance. Immersion depth 55 mm. Intermediate shelf is recommended. Appliance must be fixed from underneath.
 Cooktop clamping range: 20 - 40 mm.

Characteristics

Product name/family
 Cooking zone ceramic

Construction type
 Built-in

Energy input
 Electric

Total number of positions that can be used at the same time
 4

Type of control setting devices
 Required niche size for installation (HxWxD)
 55 x 560-560 x 490-490

Width of the product (mm)
 590

Dimensions of the product (mm)
 55 x 590 x 520

Dimensions of the packed product (HxWxD) (mm)
 126 x 753 x 603

Net weight (kg)
 16.228

Gross weight (kg)
 17.5

Residual heat indicator
 Separate

Location of control panel
 Hob front

Type of external control possibility
 Basic surface material
 Ceramic

Color of surface
 Black, Stainless steel

Color of frame
 Stainless steel

Approval certificates
 AENOR, CE

Length of electrical supply cord (cm)
 150

EAN code
 4242006266646

Consumption and connection features

Electrical connection rating (W)
 7400

Gas connection rating (W)

Current (A)

Voltage (V)
 220-240

Frequency (Hz)
 60; 50

created on 2020-02-19
 Page 1

Appliance weight: approx. 16 kg.

Connection

Total connected load 7.4 kW.
 Connecting cable 1.5 m without plug.
 Power consumption standby/display off 0.5 W.
 Power consumption standby/network 2 W.
 Please check the user manual for how to switch off the WiFi module.