



#### Color Variants

CI282111  
Stainless steel frame  
Width 80 cm

#### Optional accessories

CA051300  
Teppan Yaki plate made of multi ply material  
CA052300  
Griddle plate in cast aluminium  
CA060300  
CA230100  
Black magnetic knob for induction cooktop 200 series  
GP900001  
Stainless steel frying sensor pan  
GP900002  
Stainless steel frying sensor pan  
GP900003  
Stainless steel frying sensor pan  
GP900004  
Stainless steel frying sensor pan

CI282111  
Flex induction cooktop 200 series  
Stainless steel frame  
Width 80 cm

Sturdy stainless steel frame  
Flex function for combining the rectangular cooking areas  
Free positioning of cookware inside combined cooking areas  
Cooking sensor function for temperature control in pots  
Professional cooking function for splitting the cooktop into 3 predefined heat areas  
Frying sensor function for temperature control in pans  
Twist-Pad control with removable magnetic knob  
Easy control of all functions with two color displays

#### Cooking zones

2 flex induction cooking areas 19x24 cm (2200 W, with booster 3700 W), linked together 38x24 cm (3300 W, with booster 3700 W).  
1 induction cooking zone ø 28 cm (2400 W, with booster 3700 W).  
1 induction cooking zone ø 15 cm (1400 W, with booster 2200 W).

#### Handling

Twist-Pad control with removable magnetic knob.  
User friendly control with two color display (white / orange).  
Cooking zone, and cooking area marking.  
Electronic power control in 17 output levels.

#### Features

Flex function for rectangular cooking areas.  
Cooking sensor function (in use with cooking sensor CA 060 300).  
Professional cooking function.  
Frying sensor function.  
Booster function for pots.  
Booster function for pans.  
Keep warm function.  
Stopwatch.  
Cooking timer for up to 99 minutes.  
Short-term timer.  
Options menu.  
Power management.  
Cooktop-based ventilation control (with suitable hood).  
Integrated WiFi module for digital services (Home Connect).  
The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: [www.home-connect.com](http://www.home-connect.com)

#### Safety

Main switch.  
Operation indicator.  
Pot detection.  
2 stage Hh residual heat indicator for each zone  
Child lock.  
Safety shut-off.

#### Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.  
The wok pan WP 400 001 cannot be used with this appliance.  
Intermediate shelf is recommended.

Characteristics  
Product name/family  
Cooking zone ceramic  
Construction type  
Built-in  
Energy input  
Electric  
Total number of positions that can be used at the same time  
4  
Type of control setting devices  
Required niche size for installation (HxWxD)  
55 x 780-780 x 490-490  
Width of the appliance  
804  
Dimensions  
55 x 804 x 520  
Dimensions of the packed product (HxWxD)  
126 x 953 x 608  
Net weight  
16.356  
Gross weight  
18.0  
Residual heat indicator  
Separate  
Location of control panel  
Hob front  
Type of external control possibility  
Basic surface material  
Ceramic  
Color of surface  
Black, Stainless steel  
Color of frame  
Stainless steel  
Approval certificates  
AENOR, CE  
Length of electrical supply cord  
150  
EAN code  
4242006267025  
Electrical connection rating  
7400  
Gas connection rating  
Fuse protection  
Voltage  
220-240  
Frequency  
50; 60

#### Consumption and connection features

created on 2021-10-14  
Page 1

Appliance must be fixed from underneath.  
Appliance weight: approx. 16.  
  
**Connection**  
Total connected load 7.4 KW.  
Connecting cable 1.5 m without plug.  
Power consumption standby/display off 0.5 W.  
Power consumption standby/network 2 W.  
Please check the user manual for how to switch off the WiFi module.

