

CI283111

Optional accessories

CA051300:

Teppan Yaki (large)

CA052300:

Griddle Plate

CA230100:

Magnetic knob, black

GP900001:

System pan diameter 15 cm

GP900002:

System pan diameter 19 cm

GP900003:

Frying sensor pan Ø 21 cm

installation accessories

Flex induction hob 200 series

80 cm Cl283111

Sturdy stainless steel frame

Flex function for combining the rectangular cooking areas

Free positioning of cookware inside combined cooking areas

Frying sensor function for temperature control in pans

Twist-Pad control with removable magnetic knob Easy control of all functions with two color displays

Cooking zones

2 flex induction cooking areas 19x21 cm (2200 W, with booster 3700 W), linked together 38x21 cm (3300 W, with booster 3700 W).

- 1 induction cooking zone \varnothing 24 cm (2200 W, with booster 3700 W).
- 1 induction cooking zone \varnothing 18 cm (1800 W, with booster 3100 W).
- 1 induction cooking zone \varnothing 15 cm (1400 W, with booster 2200 W).

Handling

Twist-Pad control with removable magnetic knob.

User friendly control with two color display (white / orange).

Cooking zone, and cooking area marking. Electronic power control in 17 output levels.

Features

Flex function for rectangular cooking areas.

Frying sensor function.

Booster function for pots.

Booster function for pans.

Keep warm function.

Stopwatch.

Cooking timer for up to 99 minutes.

Short-term timer.

Options menu.

Power management.

Cooktop-based ventilation control (with suitable hood).

Integrated WiFi module for digital services (Home Connect).

The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Main switch.

Operation indicator.

Pot detection.

2 stage Hh residual heat indicator for each zone Child lock.

Safety shut-off.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.

The wok pan WP 400 001 cannot be used with this appliance.

Immersion depth 55 mm.

Intermediate shelf is recommended.

Appliance must be fixed from underneath.

Cooktop clamping range: 20 - 40 mm.

Appliance weight: approx. 19.

Connection

Total connected load 7.4 KW.

Connecting cable 1.5 m without plug.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 2 W.

Please check the user manual for how to switch off the WiFi module.





