



Color Variants

CI422101

Frameless

Width 38 cm

Optional accessories

CA051300

Teppan Yaki plate made of multi ply material

CA052300

Griddle plate in cast aluminium

GP900001

Stainless steel frying sensor pan

GP900002

Stainless steel frying sensor pan

GP900003

Stainless steel frying sensor pan

Installation Accessories

VA422000

Connection strip for combination within SETs CVL410 and CVL420.

CI422101

Flex induction cooktop 400 series

Frameless

Width 38 cm

For combination within the set CVL 410

Flex function for combining the rectangular cooking areas
Free positioning of cookware inside combined cooking areas
Frying sensor function for temperature control in pans
Easy control of all functions with two color displays
Solid stainless steel control knob
Frameless for flush installation

Cooking zones

2 flex induction cooking areas 19x24 cm (2200 W, with booster 3700 W), linked together 38x24 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring, cooking zone and output level markings.
Electronic power control in 12 stage (1...12).
User friendly control with two color display (white / orange).

Features

Flex function for rectangular cooking areas.
Frying sensor function.
Booster function.
Stopwatch.
Short-term timer.
Options menu.

Safety

Individual residual heat indicators.
Safety shut-off.

Planning notes

For combination within the sets CVL 410 and CVL 420.
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.
Appliance weight: approx. 10.

Connection

Total connected load 3.7 KW.
Connecting cable 1.5 m without plug.

Characteristics

Product name/family

Vario/Domino cooking zone cera

Construction type

Built-in

Energy input

Electric

Total number of positions that can be used at the same time

2

Required niche size for installation (HxWxD)

56 x 360-389 x 492-527

Width of the appliance

383

Dimensions

56 x 383 x 521

Dimensions of the packed product (HxWxD) (mm)

130 x 580 x 600

Net weight (kg)

10.198

Gross weight (kg)

11.2

Residual heat indicator

Location of control panel

External control

Basic surface material

Ceramic

Color of surface

Black

Color of frame

Approval certificates

AENOR, CE

Length of electrical supply cord (cm)

150

EAN code

4242006274375

Electrical connection rating (W)

3700

Gas connection rating (W)

Current (A)

Voltage (V)

220-240

Frequency (Hz)

60; 50

Consumption and connection features

created on 2021-02-24

Page 1

CI422101
Flex induction cooktop 400 series
Frameless
Width 38 cm
For combination within the set CVL 410

created on 2021-02-24
Page 2

