

Color Variants

DF480161F fully integrated with flexible hinge

Included accessories

1 x baking tray spray head.

1 x GN container insert.

1 x glass holder rack.

Optional accessories

DA042030

Silvercare cartridge for all dishwashers

Installation Accessories

GZ010011

Aqua stop extension (2 m long)

DF480161F Dishwasher 400 series

fully integrated

with flexible hinge

Height 81.5 cm

8 programmes with aqua sensor and 6 options, such as Power and Intensive:

Clean and dry dishes in 57 minutes Intensive cleaning in the lower basket while protecting glassware in the upper basket

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket

Push-to-open function for perfect integration into handleless furniture fronts

Very quiet: 43 dB

Energy efficiency class A+++ Aqua stop with guarantee

Handling

Touch key operation. Time delay up to 24 hours. Info-Light.

Features

Glass protection with zeolite. Agua sensor.

Load sensor.

Automatic detergent function. Regeneration electronics.

Heat exchanger - Hygienic and efficient drvina Continuous flow heater.

Triple filter system, self-cleaning. Soft lock. Aqua stop with guarantee.

Programmes

8 programmes:

Auto 35 °C - 45 °C.

Auto 45 °C - 65 °C.

Auto 65 °C - 75 °C. Intensive 70 °C.

Standard Eco 50 °C.

Night programme.

Quick wash 45 °C (29 min.).

Pre-rinse. 6 options:

Intensive.

Power.

Half Load.

Hygiene.

Extra Dry.

Energy Save.

Features

Flexible basket system with smooth running rails on all levels and cushioned closing of the upper and lower basket.

Upper basket: Over extension.

Rackmatic with 3 levels, adjustable in height up to 5 cm.

6 folding spines.

4 folding racks.

2 glass support bars.

Lower basket:

8 folding spines.

2 folding racks.

Dividable glass support.

Cutlery basket.

Holder for long-stemmed glasses.

12 place setting capacity.

Maximum glass loading capacity 23 wine glasses

Product rating

Energy efficiency class A+++. From 9.5 I water. From 0.8 kwh. Noise level 43 dB (re 1 pW).

Planning notes

Height-adjustable feet. Appliance plinth recess 100 mm (see drawing). AGGENAU

Characteristics

Water consumption (I) 9.5

Construction type

Built-in

Height of removable worktop (mm)

Required niche size for installation (HxWxD)

815-875 x 600 x 550

Depth with open door 90 degree (mm)

1150 Adjustable feet

Yes - front only

Maximum adjustability feet (mm)

Adjustable plinth

both horizontal and vertical

Net weight (kg)

52,270

Gross weight (kg)

55.0

Connection rating (W)

2400

Current (A)

Voltage (V)

220-240

Frequency (Hz)

50:60

Length of electrical supply cord (cm)

Plug type

Gardy plug w/ earthing Length inlet hose (cm)

Length outlet hose (cm)

EAN code

4242006260965

Consumption and connection features

Number of place settings

Energy efficiency class (2010/30/EC)

Energy consumption annual (kWh/

annum) - NEW (2010/30/EC)

Energy consumption (kWh)

0.80 Power consumption in left-on mode (W)

- NEW (2010/30/EC)

0.50 Power consumption in off-mode (W) -

NEW (2010/30/EC)

Water consumption annual (I/annum) -

NEW (2010/30/EC)

2660

Drying performance

Reference programme

Total cycle time of reference

programme (min)

Noise level (dB(A) re 1 pW)

Installation type Full-integrated

created on 2019-09-24

Page 1


Rear feet adjustable at front. Door weight up to 8.5 kg. Door panel dimension dependent on plinth height of kitchen furniture. For installation into a tall unit, ventilation openings are required (min. 200 cm²).

Connection

Total connected load 2.4 kW. Connecting cable plugable. Water connection with 3/4" screw joint. Connection to hot or cold water possible.


DF480161F
Dishwasher 400 series
fully integrated
with flexible hinge
Height 81.5 cm

created on 2019-09-24 Page 2



() Werte mit Verlängerungssatz

Connection dimensions for a 60 cm wide dishwasher



() values with extension kit

81.5 cm high dishwasher with flexible hinge

