



DV461110

Included accessories

small

50 x Vacuuming bag

big

1 x Raised vacuuming platform

1 x Adaptor f. vacuuming outside the chamber

1 x Vacuuming hose

1 x Adaptor for bottle plugs

3 x Plugs for vacuuming of bottles

Optional accessories

BA080670:

Vacuuming bags, 180 x 280 mm, 100 pcs.

BA080680:

Vacuuming bags, 240 x 350 mm, 100 pcs.

Installation Accessories

Vacuuming drawer 400 series
60 x 14 cm, Stainless steel behind glass
DV461110

- 3 vacuuming levels for vacuuming in the chamber, max. 99%
- 3 vacuuming levels for vacuuming outside the chamber, max. 90%
- 99% vacuuming inside the chamber
- Hygienic stainless steel interior with glass bottom

- Integrable in 14 cm high niche

Hygienic stainless steel vacuuming chamber, applicable height up to 95 mm

3 vacuuming levels for vacuuming in the chamber, max. 99%

3 vacuuming levels for vacuuming outside the chamber, max. 90%

Automatic connection recognition for vacuuming outside the chamber

Handleless drawer

Cushioned closing system

Application

Vacuuming for sous-vide cooking.

Vacuuming for fast marinating and flavouring.

Vacuuming for fast marinating and flavouring.

Vacuuming of vacuuming containers outside the chamber.

Vacuuming of liquids in bottles outside the chamber.

Handling

Touch key operation.

Recessed grip at the front bottom of the drawer.

Features

Net volume 7 litres.

Capacity load max. 10 kg.

Maximum size of vacuuming bags W 240 mm x L 350 mm.

3 heat-sealing levels for different strengths of bag material.

Sealing bar, non-stick coating, removable.

Safety glass cover, opens automatically after vacuuming.

Raised vacuuming platform, 44 mm, deployable.

Utility space in vacuuming chamber, W 210 mm x L 275 mm.

Membrane for avoiding reflow of liquids during vacuuming outside the chamber.

Drying programme for vacuuming pump.

Warning function.

Planning notes

The panel surface of the appliance extends 47 mm from the furniture cavity.

Installation of BS/BM/CM directly above DV in 59 cm niche without intermediate floor.

Built-in under worktop or in single niche.

The socket can be planned behind the appliance.

Connection

Total connected load 0.32 KW.

Side view of DV 461 below BS, BM, CM

