



Color Variants

RB292311
with fresh cooling
freestanding, stainless steel backed full glass doors

Included accessories

- 2 x cold accumulator.
- 1 x berry tray.
- 2 x egg tray.
- 1 x wine and champagne rack.
- 1 x glass tray.
- 1 x ice cube tray.

RB292311

Fridge-freezer combination

with fresh cooling

freestanding, stainless steel backed full glass doors

Width 70 cm, height 200 cm

Height adjustable safety glass shelves
Door racks with aluminium profiles
Net volume 395 litres
Energy efficiency class A++

Handling

Electronic temperature control with digital temperature display.
Touch keys.

Features

Dynamic cold air distribution.
Open-door and malfunction alarm.
Stainless steel top and side panels.

Cooling

No-frost technology with fast cooling.
Automatic defrosting with defrost water evaporation.
Temperature adjustable from +2 °C to +8 °C.
4 safety glass shelves, 3 of which are height adjustable.
Bright interior lighting with integrated glare-free side light elements.
1 large door rack for bottles.
5 door racks.

Fresh cooling

Net volume 46 litres.
Automatic defrosting with defrost water evaporation.
1 full width humidity drawer for vegetables with 24 litres net volume, manually controllable.
1 full width fresh cooling drawer.

Freezing

Net volume 92 litres.
No-frost technology with fast freezing.
Temperature adjustable from -16 °C to -24 °C.
4-star freezer compartment.
Automatic defrosting with defrost water evaporation.
Freezing capacity 15 kg/24 h.
Storage time after a malfunction 16 h.
3 freezer drawers.

Product rating

Energy consumption 284 kWh/year.
Noise level 43 dB (re 1 pW).

Planning notes

Door hinge right, reversible.
Wall recess of 20 mm necessary.
Door opening angle of 125°, fixable at 90°.
90 mm clearance hinge side for 90° door opening, 400 mm for 125° door opening and 65 mm handle side necessary.
If integrated in a kitchenette the body of the appliance needs a front overlap of 15 mm. Alternatively an intermediate panel can be used on the hinge side with a recess of 15 mm and a width of min. 30 mm.
Front feet are height-adjustable, casters at the back.

Connection

Total connected load 0.15 kW.
Connecting cable 2.4 m with plug.

Characteristics

Construction type

Free-standing

Door panel options

Not possible

Height (mm)

2000

Width of the product (mm)

700

Depth of the product

650

Required niche size for installation (HxWxD)

Net weight (kg)

105.661

Connection rating (W)

150

Current (A)

10

Door hinge

Right reversible

Voltage (V)

220-240

Frequency (Hz)

50

Approval certificates

CE, VDE

Length of electrical supply cord (cm)

240

Energy efficiency class

Energy consumption (kWh)

Total annual energy consumption (kWh)

Refrigerator Net capacity (l)

Freezer Net capacity (l)

Freezing capacity (kg)

Storage Period in Event of Power Failure (h)

16

Number of compressors

1

Number of independent cooling systems

2

Interior ventilator

No

Reversible Door Hinge

Yes

Number of Adjustable Shelves in fridge compartment (Stck)

3

Shelves for Bottles

Yes

EAN code

4242006231330

Consumption and connection features

Brand

Gaggenau

Product name / Commercial code

RB292311

Energy efficiency class (2010/30/EC)

A++

Energy consumption annual (kWh/annum) - NEW (2010/30/EC)

284.00

Refrigerator Net capacity (l) - NEW (2010/30/EC)

303

Freezer Net capacity (l) - NEW (2010/30/EC)

92

Frost free system

Fridge and freezer

Temperature rise time (h)

16

Freezing capacity (kg/24h) - NEW (2010/30/EC)

15

Climate class

SN-T

Noise level (dB(A) re 1 pW)

43

Installation type

N/A

created on 2019-08-29

Page 1

RB292311
Fridge-freezer combination
with fresh cooling
freestanding, stainless steel backed full
glass doors
Width 70 cm, height 200 cm
created on 2019-08-29
Page 2

