

**Color Variants** 

RF461301 fully integrated Niche width 61 cm, Niche height 213.4

### Included accessories

1 x ice cube scoop.

Required installation accessories RA460011 Additional side heating element

### Installation Accessories

RA421610

RA425110

Handle bar, stainless steel, long

RA460020

Connecting element for vertically split appliance fronts (for a flush front)

Finger protection for extra long furniture fronts

RF461301

Vario freezer 400 series

fully integrated

Niche width 61 cm, Niche height 213.4

Stainless steel interior Generous lighting concept Integrated ice maker with fixed inlet water connection Solid aluminium door racks Net volume 321 litres Energy efficiency class A+

#### Handling

Electronic temperature control with digital display.

# Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Energy-saving vacation mode Open-door and malfunction alarm.

### Freezing

No-frost technology with fast freezing. Temperature adjustable from -14 °C to -25 °C.

4-star freezer compartment. Freezing capacity 18 kg/24 h. Storage time after a malfunction 13 h. 4 solid metal shelves, 3 of which are manually adjustable.

2 fully extendable drawers with transparent front, 1 of which large, 1 regular.

Bright interior lighting with light pillars. 4 height-adjustable door racks, 1 of which is extra deep.

1 door rack with transparent front flap.

### Ice maker

Integrated, with fixed inlet water connection.

Can be switched off.

Ice cube production approx. 1.4 kg/24

Removable ice storage container with approx. 4 kg capacity.

# Product rating

Energy consumption 357 kwh/year. Noise level 41 dB (re 1 pW).

## Planning notes

Flat hinge

Door hinge left, reversible. Door opening angle of 115°, fixable at 90°

Max. door panel weight 40 kg. Shut-off valve for water connection must be planned next to the appliance and always be accessible. If the water pressure exceeds 0.8 MPa

(8 bar), connect pressure relief valve

between water tap and hose set.

# Connection

Total connected load 0.421 kW. Connecting cable 3.0 m, pluggable. Water inlet. Supply hose 3.0 m with 3/4 ' connection.

Water pressure 2.4 to 8.3 bar.

Characteristics

Thermometer freeze section

Digital

Light

**Product category** 

Upright freeze

Construction type Built-in

Door panel options Not possible

Frost free system

Fridge and freezer

Height of the product (mm)

Width of the product (mm)

Depth of the product

Required niche size for installation (HxWxD)

2134.0 x 610 x 610

Dimensions of the packed product (HxWxD) (mm)

2270 x 740 x 700

Net weight (kg)

155.854

Gross weight (kg)

171.0

Connection rating (W)

Current (A)

Frequency (Hz)

Approval certificates

CE. VDE

Length of electrical supply cord (cm)

Energy efficiency class

Energy consumption (kWh)

Total annual energy consumption (kWh)

Freezing capacity (kg)

Door hinge

Left reversible

Storage Period in Event of Power Failure (h)

Color / Material body

**Defrost process** 

Warning signal / malfunction

No signal

Lockable door

Number of drawers/baskets (Stck)

Number of freezing flaps (Stck)

EAN code

4242006217631

### Consumption and connection features

Gaggenau

Product name / Commercial code

RF461301 Product category

Upright freeze

Energy efficiency class (2010/30/EC)

Energy consumption annual (kWh/ annum) - NEW (2010/30/EC)

357.00 Freezer Net capacity (I) - NEW

(2010/30/EC)

321

Frost free system

Fridge and freezer Temperature rise time (h)

Freezing capacity (kg/24h) - NEW

(2010/30/EC)

Climate class

SN-T

Noise level (dB(A) re 1 pW)

Installation type N/A

created on 2019-04-27




RF461301 Vario freezer 400 series

fully integrated


Niche width 61 cm, Niche height 213.4 cm

created on 2019-04-27 Page 2




The hinge travel and resulting clearances from adjacent furniture units and handles can be found from the drawing while allowing for the thickness of the front panel. In the drawing, a furniture uni front panel thickness of 19 mm was assumed.





In the drawing, a unit front thickness of 19 mm and a Gaggenai unit handle of 49 mm were taken as a basis.

## Base detail



Based on the standard height of the appliance, the height of the plinth is 102 mm. Maximum thickness of the plinth is 19 mm.

