

Color Variants

RF463300 fully integrated Niche width 61 cm, Niche height 213.4

Required installation accessories Additional side heating element

Installation Accessories

RA422610

RA425110

Handle bar, stainless steel, long

RA460020

Connecting element for vertically split appliance fronts (for a flush front)

Finger protection for extra long furniture fronts

RF463300 Vario freezer 400 series

fully integrated

Niche width 61 cm, Niche height 213.4 cm

Right-hinged

Stainless steel interior Generous lighting concept Integrated ice maker with fixed inlet water connection Illuminated dispenser for ice cubes, crushed ice and chilled water Solid aluminium door racks Net volume 299 litres Energy efficiency class A+

Handling

Electronic temperature control with digital display.

Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Energy-saving vacation mode. Open-door and malfunction alarm.

No-frost technology with fast freezing. Temperature adjustable from -14 °C to -25 °C.

4-star freezer compartment. Freezing capacity 14 kg/24 h. Storage time after a malfunction 12 h. 4 solid metal shelves, 2 of which are manually adjustable.

2 fully extendable drawers with transparent front, 1 of which large, 1 regular.

Bright interior lighting with light pillars. 1 extra deep door rack.

1 door rack with transparent front flap.

Ice and water dispenser

Illuminated.

Integrated, with fixed inlet water connection.

Can be switched off.

Ice cube production approx. 1.9 kg/24

Ice cubes and crushed ice. Removable ice storage container with approx. 3 kg capacity. Ice water supply approx. 1.5 litres.

Product rating

Energy consumption 342 kwh/year. Noise level 41 dB (re 1 pW).

Planning notes

Flat hinge.

Door opening angle of 115°, fixable at

Max. door panel weight 57 kg. Shut-off valve for water connection must be planned next to the appliance and always be accessible. If the water pressure exceeds 0.8 MPa

(8 bar), connect pressure relief valve between water tap and hose set.

Connection

Total connected load 0.592 kW. Connecting cable 3.0 m, pluggable. Water inlet Supply hose 3.0 m with 3/4 " connection.

Water pressure 2.4 to 8.3 bar.

Characteristics

Thermometer freeze section

Digital

Light

Product category

Upright freeze

Construction type Built-in

Door panel options

Not possible

Frost free system Fridge and freezer

Height of the product (mm)

Width of the product (mm)

603

Depth of the product

608

Required niche size for installation (HxWxD)

2134.0 x 610 x 610

Dimensions of the packed product (HxWxD) (mm)

2270 x 750 x 700

Net weight (kg)

163.071

Gross weight (kg)

178.0

Connection rating (W)

592

Current (A)

Frequency (Hz)

Approval certificates

CE. VDE

Length of electrical supply cord (cm)

300

Energy efficiency class

Energy consumption (kWh)

Total annual energy consumption (kWh)

Freezing capacity (kg)

Door hinge

Storage Period in Event of Power Failure (h)

Color / Material body

Defrost process

Warning signal / malfunction

No signal

Lockable door

Number of drawers/baskets (Stck)

Number of freezing flaps (Stck)

EAN code

4242006219840

Consumption and connection features

Gaggenau

Product name / Commercial code

RF463300

Product category Upright freeze

Energy efficiency class (2010/30/EC)

Energy consumption annual (kWh/ annum) - NEW (2010/30/EC)

Freezer Net capacity (I) - NEW (2010/30/EC)

299

342.00

Frost free system

Fridge and freezer

Temperature rise time (h)

(2010/30/EC)

Freezing capacity (kg/24h) - NEW

Climate class

SN-T

Noise level (dB(A) re 1 pW)

Installation type N/A

created on 2019-05-06



RF463300


Vario freezer 400 series


fully integrated

Niche width 61 cm, Niche height 213.4 cm


Right-hinged


created on 2019-05-06 Page 2





— 61 — Ice D





Based on the standard height of the appliance, the height of the plinth is 102 mm. Maximum thickness of the plinth is 19 mm.

