



#### Color Variants

**RW282260**  
fully integrated, with glass door  
Niche width 56 cm, Niche height 177.2 cm

#### Optional accessories

**RA050220**  
Replacement activated charcoal air filter.

**RW282260**  
**Wine climate cabinet**  
fully integrated, with glass door  
Niche width 56 cm, Niche height 177.2 cm

Two independantly controllable climate zones  
Consistant temperatures with exact control from +5 °C to +20 °C  
Humidity control.  
Extendable bottle trays in beech and aluminium  
Presentation light option  
Low-vibration operation  
Capacity 80 bottles

#### Handling

Electronic temperature control with digital display.  
Touch keys.  
Presentation light option in each climate zone, dimmable.  
Interior lighting with automatic dimming with opening and closing of door.

#### Features

Dynamic cold air distribution.  
Automatic defrosting with defrost water evaporation.  
Cushioned door closing system integrated in door hinge.  
1 activated charcoal air filter for both climate zones.  
UV-protection.  
Open-door and malfunction alarm.  
Child lock.

#### Features

Net volume 254 litres.  
Capacity 80 bottles (based on 0.75/l standard bottles).  
10 bottle trays, 8 of which are extendable.  
Storage of magnum bottles possible.  
LED lighting.

#### Product rating

Energy consumption 160 kWh/year.  
Noise level 35 dB (re 1 pW).

#### Planning notes

Flat hinge.  
Door hinge right, reversible.  
Height-adjustable feet.  
Door opening angle of 115°, fixable at 90°.  
Max. door panel weight 20 kg.  
Door panel thickness min. 16 mm/ max.22mm.  
The main socket needs to be planned outside of the niche.  
For a side-by-side installation every appliance must be planned in its own niche.  
When combining the wine climate cabinet with cooling appliances other than a second wine climate cabinet, these must have side heating to avoid condensation. Without side heating a clearance of min. 150 mm is to be kept between the appliances.  
No transport/operation above 1.500 m sea level.

#### Connection

Total connected load 0.130 kW.  
Connecting cable 2.8 m, pluggable.

#### Characteristics

<b>Construction type</b>	Built-in
<b>Door panel options</b>	Possible but accessory
<b>Height (mm)</b>	1770
<b>Width of the product (mm)</b>	557
<b>Depth of the product</b>	553
<b>Required niche size for installation (HxWxD)</b>	1772.0 x 560 x 550
<b>Net weight (kg)</b>	90.000
<b>Connection rating (W)</b>	130
<b>Current (A)</b>	10
<b>Interior ventilator</b>	No
<b>Voltage (V)</b>	220-240
<b>Frequency (Hz)</b>	50
<b>Approval certificates</b>	CE, VDE
<b>Length of electrical supply cord (cm)</b>	280
<b>Plug type</b>	Gardy plug w/ earthing
<b>Energy consumption (kWh/d) winecooler</b>	
<b>Energy consumption per Year (kWh/a) winecooler</b>	
<b>Total unit gross capacity (l)</b>	289
<b>Number of compressors</b>	1
<b>Number of independent cooling systems</b>	2
<b>Reversible Door Hinge</b>	Yes
<b>Interior light switch</b>	No
<b>EAN code</b>	4242006278816

#### Consumption and connection features

<b>Brand</b>	Gaggenau
<b>Product name / Commercial code</b>	RW282260
<b>Product category</b>	
<b>Energy efficiency class (2010/30/EC)</b>	A
<b>Energy consumption annual (kWh/ annum) - NEW (2010/30/EC)</b>	160.00
<b>Capacity in 0.75l (bordeaux bottles)</b>	80
<b>Climate class</b>	SN
<b>Noise level (dB(A) re 1 pW)</b>	35

created on 2020-03-05

Page 1

# GAGGENAU