

Color Variants

RW414361

fully integrated, with glass door Niche width 45.7 cm, Niche height 213.4

Optional accessories

RA491131

Fully extendable bottle tray in beech and aluminium

RA492130

Fully extendable shelves in aluminium

Required installation accessories

RA460011

Additional side heating element

Installation Accessories

RA420010

Door lock RA421111

RA421112

RA425110

Handle bar, stainless steel, long

RA460040

Finger protection for extra long

furniture fronts

RW414361

Vario wine climate cabinet 400 series

fully integrated, with glass door

Niche width 45.7 cm, Niche height 213.4 cm

climate zones Consistant temperatures with exact control from +5 °C to +20 °C **Humidity control** Stainless steel interior Fully extendable bottle trays in beech and aluminium Presentation light option

Two independantly controllable

Low-vibration operation Capacity 70 bottles

Aluminium profiles of bottle travs and presenters for single bottle display can be labeled with Stabilo All 8046 pencil.

Handling

Electronic temperature control with digital display.

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Antimicrobial activated charcoal air filter.

UV-protection.

Energy-saving vacation mode. Open-door and malfunction alarm.

Features

Net volume 271 litres. Capacity 70 bottles (based on 0.75/I standard bottles).

10 fully extendable bottle trays, up to 4 of which for storage of magnum bottles.

Space for max. 14 bottle trays or shelves in aluminium.
Interior lighting with 2 ceiling spots

in the upper and 1 ceiling spot in the lower climate zone, can be used as presentation light.

Product rating

Energy efficiency class B. Energy consumption 228 kwh/year. Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.

Door hinge right, reversible. Door opening angle of 115°, fixable at

Max. door panel weight 72 kg. The main socket needs to be planned outside of the niche.

No transport/operation above 1.500 m sea level.

Connection

Total connected load 0.121 kW. Connecting cable 3.0 m, pluggable. Characteristics

Construction type

Built-in

Door panel options

Not possible

Height (mm) 2125

Width of the product (mm)

451

Depth of the product

Required niche size for installation (HxWxD)

2134.0 x 457.0 x 610

Net weight (kg)

129.000

Connection rating (W)

121

Current (A)

Interior ventilator

Voltage (V)

220-240

Frequency (Hz)

Approval certificates

CE, VDE

Length of electrical supply cord (cm) 300

Plug type Gardy plug w/ earthing

Energy consumption (kWh/d) winecooler

0.62

Energy consumption per Year (kWh/a) winecooler

227.8

Total unit gross capacity (I)

311 Number of compressors

Number of independent cooling systems

Reversible Door Hinge Yes

Interior light switch

EAN code

4242006217594

Consumption and connection features

Gaggenau Product name / Commercial code

RW414361

Product category

Winestorage

Energy efficiency class (2010/30/EC)

Energy consumption annual (kWh/ annum) - NEW (2010/30/EC) 228.00

Capacity in 0.75l (bordeaux bottles)

Climate class

Noise level (dB(A) re 1 pW)

created on 2019-04-30

Page 1



RW414361


Vario wine climate cabinet 400 series


fully integrated, with glass door

Niche width 45.7 cm, Niche height 213.4 cm

created on 2019-04-30 Page 2


Bottle storag






72-106 The maximum door panel dimensions are based on a clearance of 3 m

Door opening angle




The hinge travel and resulting clearances from adjacent furniture units and handles can be found from the drawing while allowing for the thickness of the front panel. In the drawing, a furniture unit front panel thickness of 19 mm was assumed.





In the drawing, a unit front thickness of 19 mm and a Gaggena unit handle of 49 mm were taken as a basis.

Base detail



Based on the standard height of the appliance, the height of the