

Color Variants VE270114 Stainless steel control panel Width 70 cm

Included accessories

1 x glass scraper.

Installation Accessories VV200014 Stainless steel connection strip

for combination with further Vario cooktops VE270114 Vario glass ceramic cooktop 200 series Stainless steel control panel Width 70 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity.

Generous control panel for comfortable and secure operation.

Cooking zones

 Super-Quick cooking zone ø 14.5 cm (1100 W), converts to 14.5 x 24 cm (2000 W) roasting zone.
 Super-Quick cooking zone ø 14.5 cm (1000 W), converts to ø 21 cm (2200 W) cooking zone.
 Super-Quick cooking zone ø 18 cm (1800 W).
 Super-Quick cooking zone ø 14.5 cm (1200 W).

Handling

Continuously variable energy controls.

Features Cooking zone marking.

Safety Individual residual heat indicators. Operation indicator.

Planning notes

Immersion depth 58 mm. Under the appliance, a 60 mm clearance must be observed from side panels or intermediate shelf must be planned. Appliance can be snapped into the worktop from above. Securing rail on the rear and the front.

Connection

Total connected load 7.2 kW. Plan a connection cable.

Characteristics

Product name/family Cooking zone ceramic Construction type Built-in Energy input Electric Total number of positions that can be used at the same time

4 Type of control setting devices Required niche size for installation

(HxWxD) 58 x 680-680 x 490-490 Width of the product (mm) 700 Dimensions of the product (mm) 58 x 700 x 523 Dimensions of the packed product (HxWxD) (mm) 193 x 810 x 600 Net weight (kg) 13.741 Gross weight (kg) 15.0 Residual heat indicator Separate Location of control panel Hob front Type of external control possibility

Basic surface material Ceramic Color of surface

Black, Black

Color of frame

Black Approval certificates CE, Eurasian, Ukraine, VDE Length of electrical supply cord (cm)

EAN code 4242006190538

Consumption and connection features Electrical connection rating (W) 7200

 Gas connection rating (W)

 Current (A)

 3*16

 Voltage (V)

 230

 Frequency (Hz)

 60; 50

created on 2019-11-08 Page 1



