



VF414110
Vario deep fryer 400 series
Stainless steel
Width 38 cm

Three-zone basin, without flavour transfer
Exact temperature control, no drop in output
Integrated frying basket suspension
Solid stainless steel control knob
Precision crafting of 3 mm stainless steel
For surface installation with a visible edge or for flush installation
Can be combined perfectly with other Vario appliances of the 400 series

Cooking zones
 Three-zone basin.
 Oil capacity 3.5 litres.

Handling
 Control knobs with illuminated ring, oil/fat selection and temperature marking.
 Electronic temperature control from 135 °C to 190 °C, in 5 °C steps.

Features
 Cleaning setting.
 Gentle fat melting setting.
 Foaming zone.
 Frying zone.
 Cold oil zone.
 Swing-out heating element (3000 W).

Safety
 Oil drain valve with child lock.
 Safety shut-off.

Planning notes
 Depending on the type of installation (surface-mounted or flush-mounted, with or without an appliance cover), the specific location of the cut-out and the knob positions may vary.
 If installing with the appliance cover VA 440 or adjustment strip VA 450 take into account the additional space required for the depth.
 If combining several appliances with at least one appliance cover, the adjustment strip VA 450 is required to compensate for the depth of the appliance without the appliance cover.
 If combining several Vario appliances of the 400 series, a connection strip VA 420 must be placed between the appliances. Depending on the type of installation, the corresponding connection strip must be provided.
 In the cut-out, the installation system requires the side edge to be at least 10 mm for surface installation and at least 13 mm for flush installation. Ensure a continuous cut surface of 90°.
 The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. Additional instructions for flush installation:
 Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.
 The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.

Characteristics
Product name/family
 Vario/Domino deep fryer
Construction type
 Built-in
Energy input
 Electric
Type of control
 Electronic
Type of control setting and signalling devices
 Cylindrical controls
Required niche size for installation (HxWxD)
 270 x 360 x 490
Width of the product (mm)
 380
Dimensions of the product (mm)
 270 x 380 x 520
Dimensions of the packed product (HxWxD) (mm)
 380 x 451 x 590
Net weight (kg)
 12.945
Gross weight (kg)
 15.5
Power on indicator
 Yes
Location of control panel
Type of regulation
 Stepless energy regulated
Basic surface material
 Stainless steel
Color of surface
 Stainless steel, Stainless steel
Color of frame
 Stainless steel
Approval certificates
 Australia Standards, CE, China, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (cm)
EAN code
 4242006213244

Consumption and connection features
Electrical connection rating (W)
 3000
Current (A)
 16
Voltage (V)
 220-240
Frequency (Hz)
 60; 50
created on 2020-04-02
Page 1

The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.
 If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.
 Plan a door in the bottom cabinet for operation of the oil drain valve.
 Built-in control panel to be integrated in the bottom cabinet at drawer level.
 Panel thickness 16 – 26 mm.
 The drawing "Installation of the control knob" must be observed if the panel is more than 26 mm thick (there must be a recess at the rear).
 VF 414 and VK 414 must not be installed directly next to each other.
 A minimum clearance of at least 40 mm from the appliance edge to the wall or to adjacent furniture must be observed.
 Appliance can be snapped into the worktop from above.
 Appliance weight: approx. 13 kg.

Connection
 Total connected load 3.0 kW.
 Plan a connection cable.

Color Variants
VF414110
Stainless steel
Width 38 cm

Included accessories
 1 x deep-fat frying basket.

Installation Accessories
VA420000
 Connection strip for combination with other Vario appliances of the 400 series for flush installation
VA420001
 Connection strip for combination with other Vario appliances of the 400 series for flush installation with appliance cover/adjustment strip
VA420010
 Connection strip for combination with other Vario appliances of the 400 series for surface installation
VA420011
 Connection strip for combination with other Vario appliances of the 400 series for surface installation with appliance cover/adjustment strip
VA440010
 Stainless steel appliance cover with mounting strip
VA450400
 Stainless steel adjustment strip 38 cm