



Color Variants

VI230114  
Stainless steel control panel  
Width 28 cm

Installation Accessories

SH230001  
Hinge holder for fitting the appliance cover  
VV200014  
Stainless steel connection strip for combination with further Vario cooktops

VI230114  
Vario induction cooktop 200 series  
Stainless steel control panel  
Width 28 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity.  
Generous control panel for comfortable and secure operation.

Cooking zones  
1 induction cooking zone ø 21 cm (2200 W, with booster 3300 W).  
1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling  
Control knobs with cooking zone and output level markings.  
Electronic power control in 9 output levels.

Features  
Cooking zone marking.  
Pot detection.  
Booster function for both cooking zones.

Safety  
Residual heat indication.  
Operation indicator.  
Safety shut-off.

Planning notes  
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. Immersion depth 50 mm.  
The wok pan WP 400 001 cannot be used with this appliance.  
Appliance must be fixed from underneath.  
Cooktop clamping range: 20 - 40 mm.

Connection  
Total connected load 3.7 kW.  
Connecting cable 1.5 m without plug.

Characteristics  
Product name/family  
Vario/Domino cooking zone cera  
Built-in / Free-standing  
CONSTR\_TYPE.Built-in  
Energy input  
Electric  
Total number of positions that can be used at the same time  
2  
Required niche size for installation (HxWxD)  
50 x 268 x 490  
Width of the product (mm)  
288  
Dimensions of the product (mm)  
50 x 288 x 523  
Dimensions of the packed product (HxWxD) (mm)  
175 x 400 x 605  
Net weight (kg)  
6.581  
Gross weight (kg)  
8.0  
Residual heat indicator  
Separate  
Location of control panel  
Hob front  
Basic surface material  
Ceramic  
Color of surface  
Black, Stainless steel  
Color of frame  
Stainless steel  
Approval certificates  
AENOR, CE  
Length of electrical supply cord (cm)  
150  
EAN code  
4242006194291

Consumption and connection features  
Electrical connection rating (W)  
3700  
Gas connection rating (W)  
Current (A)  
Voltage (V)  
220-240  
Frequency (Hz)  
50; 60

created on 2019-10-23  
Page 1

