

VI422103

Optional accessories

CA051300:

Teppan Yaki (large)

CA052300:

Griddle Plate

GP900001:

System pan diameter 15 cm

GP900002:

System pan diameter 19 cm

GP900003:

Frying sensor pan Ø 21 cm

installation accessories

Vario flex induction cooktop 400 series

38 cm

VI422103

- Solid stainless steel knob, also in black robust finishing, for precise control and personalisation

- Flex function for combining the rectangular cooking areas

Flexible positioning of cookware inside combined cooking areas

Frying sensor function for temperature control in pans

Easy control of all functions with two color displays

Solid stainless steel control knob

Frameless for flush installation

For combination within the sets CVL 410 and CVL 420

Cooking zones

2 flex induction cooking areas 24x20 cm (2200 W, with booster 3700 W), linked together 24x40 cm (3300 W, with booster 3700 W).

Handling

Control knobs with illuminated ring, cooking zone and output level markings.

Electronic power control in 12 stage (1...12).

User friendly control with two color display (white / orange).

Features

Flex function for rectangular cooking areas.

Frying sensor function.

Booster function.

Stopwatch.

Short-term timer.

Options menu.

Power management.

Cooktop-based ventilation control (with suitable hood).

Integrated WiFi module for digital services (Home Connect).

The availability of the Home Connect functionality depends on the availability of the Home Connect Services in your country. Home Connect Services are not available in every country – for further information please check: www.home-connect.com

Safety

Operation indicator.

Pot detection.

2 stage Hh residual heat indicator for each zone

Safety shut-off.

Planning notes

The horizontal positioning of the knobs may be aligned with the specific cooking areas.

The drawing "Installation of the control knob" must be observed if the panel is more than 23 mm thick (there must be a recess at the rear).

The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads.

Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.

The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.

The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.

If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.

Appliance can be snapped into the worktop from above.

Appliance weight: approx. 10.

Connection

Total connected load 3.7 KW.


Connecting cable 1.50 m without plug.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.4 W.


Please check the user manual for how to switch off the WiFi module.

View from above




measurements in mm

Installation of the control knob; flush installation




measurements in mm

Cross-section



- A: 6.5^{+0.5}
- B: 1.5
- C: Fill with silicone


measurements in mm



- A: 6.5^{+0.5}

measurements in mm

Longitudinal section



- A: 6.5^{+0.5}
- B: 2.5
- C: 14.5
- D: Fill with silicone

measurements in mm