



**VK414110**  
**Vario steamer 400 series**  
**Stainless steel**  
**Width 38 cm**

**Steaming in cooktop size**  
**Exact water temperature control from 45 °C to 95 °C**  
**Cooking on two levels, without flavour transfer**  
**Solid stainless steel control knob**  
**Precision crafting of 3 mm stainless steel**  
**For surface installation with a visible edge or for flush installation**  
**Can be combined perfectly with other Vario appliances of the 400 series**

**Cooking zones**  
 Water capacity 1 to 6 litres.

**Handling**  
 Control knobs with illuminated ring, temperature markings and outlet water. Electronic water temperature control from 45 °C to 95 °C, in 5 °C steps.

**Features**  
 Steam cooking level with electronic steam control for pressureless cooking. Automatic boiling point detection. Motor-driven 1/2" water drain valve.

**Safety**  
 Safety shut-off.

**Planning notes**  
 Depending on the type of installation (surface-mounted or flush-mounted, with or without an appliance cover), the specific location of the cut-out and the knob positions may vary.  
 If installing with the appliance cover VA 440 or adjustment strip VA 450 take into account the additional space required for the depth.  
 If combining several appliances with at least one appliance cover, the adjustment strip VA 450 is required to compensate for the depth of the appliance without the appliance cover.  
 If combining several Vario appliances of the 400 series, a connection strip VA 420 must be placed between the appliances. Depending on the type of installation, the corresponding connection strip must be provided.  
 In the cut-out, the installation system requires the side edge to be at least 10 mm for surface installation and at least 13 mm for flush installation. Ensure a continuous cut surface of 90°.  
 The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. Additional instructions for flush installation:  
 Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.  
 The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.  
 The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.  
 If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.

**Characteristics**  
**Product name/family**  
 Vario/Domino steam cooker  
**Construction type**  
 Built-in  
**Energy input**  
 Electric  
**Type of control**  
 Electronic  
**Type of control setting and signalling devices**  
 Cylindrical controls  
**Required niche size for installation (HxWxD)**  
 290 x 360 x 490  
**Width of the product (mm)**  
 380  
**Dimensions of the product (mm)**  
 290 x 380 x 520  
**Dimensions of the packed product (HxWxD) (mm)**  
 374 x 458 x 590  
**Net weight (kg)**  
 14.311  
**Gross weight (kg)**  
 16.8  
**Power on indicator**  
 Yes  
**Location of control panel**  
**Type of regulation**  
 Stepless energy regulated  
**Basic surface material**  
 Stainless steel  
**Color of surface**  
 Stainless steel, Stainless steel  
**Color of frame**  
 Stainless steel  
**Approval certificates**  
 Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (cm)**  
**EAN code**  
 4242006213497

**Consumption and connection features**  
**Electrical connection rating (W)**  
 2000  
**Current (A)**  
 10  
**Voltage (V)**  
 220-240  
**Frequency (Hz)**  
 60; 50  
 created on 2020-02-19  
 Page 1

Built-in control panel to be integrated in the bottom cabinet at drawer level. Panel thickness 16 – 26 mm. The drawing "Installation of the control knob" must be observed if the panel is more than 26 mm thick (there must be a recess at the rear). Seal the worktop cutout. VK 414 and VF 414 must not be installed directly next to each other. A minimum lateral clearance of at least 40 mm from adjacent heat-sensitive furniture. In case of suspended cabinets a ventilation hood must be installed above the steamer. If a cover is fitted, the glass lid must be removed when closing it. Appliance can be snapped into the worktop from above. Appliance weight: approx. 14 kg.

**Connection**  
 Total connected load 2.0 kW. Plan a connection cable.

**Color Variants**  
**VK414110**  
**Stainless steel**  
**Width 38 cm**

**Included accessories**  
 2 x cooking insert.  
 1 x glass cover.  
 1 x hand grip.  
 1 x residuary filter.  
 1 x water drain valve.

**Optional accessories**  
**FK023000**  
**GE020010**  
**Unperforated cooking insert**  
**GE020020**  
**Perforated cooking insert**

**Installation Accessories**  
**AG050000**  
 Drain installation set with check valve drain set (DN 40) and connecting sleeve (1/2" on 1 1/2")  
**AG060000**  
 Drain installation set enables drainage of cooking liquid into a suitable receptacle  
**VA420000**  
 Connection strip for combination with other Vario appliances of the 400 series for flush installation  
**VA420001**  
 Connection strip for combination with other Vario appliances of the 400 series for flush installation with appliance cover/adjustment strip  
**VA420010**  
 Connection strip for combination with other Vario appliances of the 400 series for surface installation  
**VA420011**  
 Connection strip for combination with other Vario appliances of the 400 series for surface installation with appliance cover/adjustment strip  
**VA440010**  
 Stainless steel appliance cover with mounting strip  
**VA450400**  
 Stainless steel adjustment strip 38 cm

VK414110


Vario steamer 400 series

Stainless steel

Width 38 cm


created on 2020-02-19

Page 2




Drainage into a water-collecting receptacle (e.g. saucepan). Only possible with AG 060 000 drain installation set.

Keep bottom drain valve at the back accessible through the door in the base unit.



Drainage connection present in the bottom cupboard:  
For a fixed connection without free fall section as per DIN 1986 Part 1, a non-return valve must be installed.  
Recommendation: AG 050 000 Drain installation set.



Sewer connection present in the base unit:  
If there is a fixed connection with a free fall section as per DIN 1986 Part 1, it is recommended that you install a non-return valve.  
Recommendation: AG 050 000 drain installation set.