



Color Variants

VL041115
Stainless steel control panel
Width 8.5 cm

Installation Accessories

AD724042
LS041001
Stainless steel
VV200014
Stainless steel connection strip
for combination with further Vario
cooktops

VL041115
Vario downdraft ventilation 200 series
Stainless steel control panel
Width 8.5 cm
Control unit
Air extraction/air recirculation with
remote fan unit AR 403/413 121

Ventilation element integrated in the
worktop
Highly efficient ventilation system
close to the cooktop
Minimal planning and easy
installation for air recirculation

Output

Maximum air output in combination
with remote fan units s. table remote
fan units on page xxx.

Features

Output control, knob operation.
4 output levels.
Ventilation grille can be washed.
Metal grease filter with grease
collecting insert.
No duct connection piece included.

Product rating

Consumption data is referred to a
configuration with the remote fan unit
AR 403 121.
Energy consumption xxx.
Ventilation efficiency class B.
Grease filter efficiency class D.
Sound level min. 52 dB / max. 67 dB
normal mode.

Planning notes

No additional switch necessary.
Air extraction in combination with
remote fan unit AR 403 121 or air
recirculation mode with AR 413 121.
Please refer to page xxx for
recommended configurations of
downdraft ventilations and remote fan
units and the needed ducting elements.
Maximum cooktop width between two
VL: 60 cm (exception: VI/VE 270).
If installed next to gas appliances,
the ventilation moulding LS 041 001
is recommended to ensure maximum
performance of the cooktop. If installed
next to gas appliances, flat ducts must
not be used for the piping up to the fan
unit.
When having installed the ventilation
moulding LS 041 001 the wok pan WP
400 001 can not be used.
When installing a ventilation hood with
air extraction mode or recirculation
outlet in another area of room air (e.g.
cellar) and a chimney-vented fireplace,
the hood's power supply line needs a
suitable safety switch.

Connection

Connecting cable 1.5 m with plug.

Characteristics

Product name/family
Color chimney
Typology
Approval certificates
Australia Standards, CE, Eurasian, G-
Mark, Ukraine, VDE
Length of electrical supply cord (cm)
150
Required niche size for installation
(HxWxD)
320mm x 78.0mm x 490mm
Height of the chimney (mm)
Height of product, without chimney
(mm)
Minimum distance above an electric
hob
Minimum distance above a gas hob
Net weight (kg)
2.535
Type of control
mechanical
Number of speed settings
4
Maximum output air extraction (m3/h)
440
Boost position output recirculating
(m3/h)
Maximum output recirculating air (m3/
h)
Boost position air extraction (m³/h)
Number of lights (Stck)
Noise level (dB(A) re 1 pW)
67
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
EAN code
4242006239770

Consumption and connection features

Connection rating (W)

Current (A)

10

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

Installation type

Built-in

created on 2020-02-20

Page 1