



VP414110

Vario teppan yaki 400 series

Stainless steel

Width 38 cm

Cooking directly on the hard-chromed metal surface, without any pots or pans
Exact temperature control up to 240 °C
Optimum heat distribution
Solid stainless steel control knob
Precision crafting of 3 mm stainless steel
For surface installation with a visible edge or for flush installation
Can be combined perfectly with other Vario appliances of the 400 series

Cooking zones

Usable area W 31 x D 44 cm.

Handling

Control knobs with illuminated ring, cooking zone and temperature markings.
Electronic temperature control from 120 °C to 240 °C.

Features

Two zones, each 1500 W, can be operated together as a complete surface or each half separately. Keeping warm setting.
Even with traces of use, always easy to clean like a cast pan.

Safety

Safety shut-off.

Planning notes

Depending on the type of installation (surface-mounted or flush-mounted, with or without an appliance cover), the specific location of the cut-out and the knob positions may vary.
If installing with the appliance cover VA 440 or adjustment strip VA 450 take into account the additional space required for the depth.
If combining several appliances with at least one appliance cover, the adjustment strip VA 450 is required to compensate for the depth of the appliance without the appliance cover.
If combining several Vario appliances of the 400 series, a connection strip VA 420 must be placed between the appliances. Depending on the type of installation, the corresponding connection strip must be provided.
In the cut-out, the installation system requires the side edge to be at least 10 mm for surface installation and at least 13 mm for flush installation. Ensure a continuous cut surface of 90°.
The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. Additional instructions for flush installation:
Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.
The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.
The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.

Characteristics

Product name/family

Vario/Domino Teppan Yaki

Construction type

Built-in

Energy input

Electric

Type of control

Electronic

Grill grating material

Required niche size for installation (HxWxD)

72 x 360 x 490

Width of the product (mm)

380

Dimensions of the product (mm)

72 x 380 x 520

Dimensions of the packed product (HxWxD) (mm)

232 x 455 x 593

Net weight (kg)

13.562

Gross weight (kg)

14.8

Residual heat indicator

Separate

Location of control panel

Hob front

Basic surface material

Color of surface

Stainless steel, Stainless steel

Color of frame

Stainless steel

Approval certificates

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (cm)

EAN code

4242006213510

Consumption and connection features

Electrical connection rating (W)

3000

Gas connection rating (W)

Current (A)

16

Voltage (V)

220-240

Frequency (Hz)

60; 50

created on 2020-07-25

Page 1

If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.
Built-in control panel to be integrated in the bottom cabinet at drawer level. Panel thickness 16 – 26 mm.
The drawing "Installation of the control knob" must be observed if the panel is more than 26 mm thick (there must be a recess at the rear).
A minimum lateral clearance of at least 40 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted. Appliance can be snapped into the worktop from above.
Appliance weight: approx. 14.

Connection

Total connected load 3.0 KW.
Plan a connection cable.

Color Variants

VP414110

Stainless steel

Width 38 cm

Included accessories

2 x spatula.

Installation Accessories

VA420000

Connection strip for combination with other Vario appliances of the 400 series for flush installation

VA420001

Connection strip for combination with other Vario appliances of the 400 series for flush installation with appliance cover/adjustment strip

VA420010

Connection strip for combination with other Vario appliances of the 400 series for surface installation

VA420011

Connection strip for combination with other Vario appliances of the 400 series for surface installation with appliance cover/adjustment strip


VA440010

Stainless steel appliance cover with mounting strip


VA450400

Stainless steel adjustment strip 38 cm


Installation of the control knob; surface mounting




Installation of the control knob; flush installation




Installation with appliance cover/spacer batten;
 installation standing proud of surrounding surfaces



Installation with appliance cover/spacer batten;
 installation flush with surrounding surfaces




Cross-section





When installing with appliance cover or filler strip, pay attention to the deeper cut-out and the front and rear groove width.

View from above




* with appliance cover or filler strip (observe the front and rear asymmetrical support, see separate notes "Installation with appliance cover/filler strip").


Longitudinal section



* with appliance cover or filler strip.
 See separate planning notes.
 ** 83 mm in the area of the cable clamp (right, centre).




* with appliance cover or filler strip.
 See separate planning notes.
 ** 80 mm in the area of the cable clamp (right, centre).





380	Appliance
3	Connection strip
804	Appliance
1197	Appliance
250	Cable clamp
1197±2	Cut-out




Without cover




With cover/spacer bottom



380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1372	Appliance
250	Cable clamp
1392±2	Cut-out




110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1292	VL
-20	Overhang
1292	Cut-out






110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1981	VL
-20	Overhang
1981	Cut-out




380	Appliance
3	Connection strip
550	Appliance
3	Connection strip
380	Appliance
1362	VL
-20	Overhang
1362	Cut-out
+20	Overhang
-6	Silicone joint
1362	Cut-out with groove




380	Appliance
3	Connection strip
804	Appliance
1183	VL
-20	Overhang
1183	Cut-out
+20	Overhang
-6	Silicone joint
1183	Cut-out with groove




380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1372	VL
-20	Overhang
1372	Cut-out
+20	Overhang
-6	Silicone joint
1372	Cut-out with groove




- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 1312
- 20 Overhang
- 1292 Cutout
- +20 Overhang
- 48 Silicone joint
- 1318 Cutout with groove




- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 1981
- 20 Overhang
- 1961 Cutout
- +20 Overhang
- 48 Silicone joint
- 1981 Cutout with groove



Without cover




With cover/spacer battens






380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
1146	Appliance
-20	Overhang
1126	Cutout




380	Appliance
3	Connection strip
590	Appliance
3	Connection strip
380	Appliance
1356	Appliance
-20	Overhang
1336	Cutout




Without cover




With cover/spacer bottom




380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
1146	Appliance
-20	Overhang
1126	Cutout
+20	Overhang
-46	Spacers part
1152	Cut-out with groove




110	VL
3	Connection strip
590	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1196	Appliance
-20	Overhang
1176	Cutout
+20	Overhang
-46	Spacers part
1200	Cut-out with groove




110	VL
3	Connection strip
590	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1196	Appliance
-20	Overhang
1179	Cutout




- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 1868 Overhang
- 1848 Cut-out



- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 1868 Overhang
- 1848 Cut-out
- 120 Overhang
- 1614 Cut-out with groove



- 380 Appliance
- 3 Appliance
- 110 VL
- 3 Connection strip
- 380 Appliance
- 876 Overhang
- 892 Cut-out



- 380 Appliance
- 3 Connection strip
- 110 VL
- 3 Connection strip
- 380 Appliance
- 876 Overhang
- 892 Cut-out
- 120 Overhang
- 1614 Cut-out with groove