



Color Variants

VI260114
Stainless steel control panel
Width 60 cm

VI260114
Vario induction cooktop 200 series
Stainless steel control panel
Width 60 cm

Can be combined with the cooktops of the Vario 200 series to a harmonic unity
Generous control panel for comfortable and secure operation

Cooking zones
1 induction cooking zone ø 21 cm (2200 W, with booster 3700 W).
2 induction cooking zones ø 18 cm (1800 W, with booster 2500 W).
1 induction cooking zone ø 15 cm (1400 W, with booster 1800 W).

Handling
Control knobs with cooking zone and output level markings.
Electronic control in 9 output levels.

Features
Cooking zone marking.
Pot detection.
Booster function for all cooking zones (two cooking zones - left and right - can be operated simultaneously with booster function).

Safety
Residual heat indication.
Operation indicator.
Safety shut-off.

Planning notes
Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended.
Immersion depth 49 mm.
Cooktop clamping range: 20 - 40 mm.
Intermediate shelf is recommended.
Appliance must be fixed from underneath.
Appliance weight: approx. 13 kg.

Connection
Total connected load 7.4 kW.
Connecting cable 1.5 m without plug.

Characteristics
Product name/family
Cooking zone ceramic
Construction type
Built-in
Energy input
Electric
Total number of positions that can be used at the same time
4
Type of control setting devices
Required niche size for installation (HxWxD)
49 x 560-560 x 490-490
Width of the product (mm)
580
Dimensions of the product (mm)
49 x 580 x 523
Dimensions of the packed product (HxWxD) (mm)
113 x 1091 x 709
Net weight (kg)
12.970
Gross weight (kg)
14.0
Residual heat indicator
Separate
Location of control panel
Hob front
Type of external control possibility
Basic surface material
Ceramic
Color of surface
Black, Stainless steel
Color of frame
Stainless steel
Approval certificates
AENOR, CE
Length electrical supply cord (cm)
150
Knob Material
Full metal
Sealed Burners
No
Heating with booster
All
Type of pan support
Natural Gas Connection Rating (BTU)
LP Gas Connection Rating (BTU)
Dimension of 1st heating element (in)
Power of heating element (kW)
1.8
Power of 1st burner (BTU)
Dimension of 2nd heating element (in)
Power of 2nd heating element (kW)
Power of 2nd burner (BTU)
Dimension of 3rd heating element (in)
Power of 3rd heating element (kW)
1.8
Power of 3rd burner (BTU)
Dimension of 4th heating element (in)
Power of 4th heating element (kW)
Power of 4th burner (BTU)
Dimension of 5th heating element (in)
Power of 5th heating element (kW)
1.4
Power of 5th burner (BTU)
Dimension of 6th heating element (in)
Power of heating element (kW in boost)
[2.5]
Power of 2nd heating element (kW in boost)
Power of 3rd heating element (kW in boost)
[2.5]
Power of 4th heating element (kW in boost)
Power of 5th heating element (kW in boost)
[1.8]
Power of 6th heating element (kW in boost)

Consumption and connection features
Electrical connection rating (W)
7400
Gas connection rating (W)
Current (A)
Voltage (V)
220-240

