



Color Variants

VL040115
Stainless steel control panel
Width 8.5 cm

VL040115
Vario downdraft ventilation 200 series
Stainless steel control panel
Width 8.5 cm
Expansion element
Air extraction/air recirculation with remote fan unit AR 403/413 121

Ventilation element integrated in the worktop
Highly efficient ventilation system at the cooktop
Minimal planning and easy installation for air recirculation

Output

Power levels depend on the remote fan unit, see table on page XX.

Features

Ventilation grille, washable.
Metal grease filter with grease drip tray, dishwasher-safe.
No duct connecting piece included.

Planning notes

Only in combination with VL 041 115.
Air extraction in combination with remote fan unit AR 403 121 or air recirculation mode with AR 413 121.
Please refer to page xxx for recommended configurations of downdraft ventilations and remote fan units and the needed ducting elements.
Maximum cooktop width between 2 VL: 60 cm (exception: VI/VE 270).
If installed next to gas appliances, the ventilation moulding LS 041 001 is recommended to ensure maximum performance of the cooktop. If installed next to gas appliances, flat ducts must not be used for the piping up to the fan unit.
When having installed the ventilation moulding LS 041 001 the wok pan WP 400 001 can not be used.
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.
Please read additional planning notes on page xx.

When having installed the ventilation moulding LS 041 001 the wok pan WP 400 001 can not be used.
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.
Please read additional planning notes on page xx.

Connection

Connecting cable 2.0 m with plug.

Characteristics
Product name/family
Color chimney
Typology
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
200
Required niche size for installation (HxWxD)
320mm x 78.0mm x 490mm
Height of the chimney (mm)
Height of product, without chimney (mm)
Net weight (kg)
1.335
Type of control
Number of speed settings
Maximum output air extraction (m3/h)
Boost position output recirculating (m3/h)
Maximum output recirculating air (m3/h)
Boost position air extraction (m³/h)
Number of lights
Noise level (dB)
Diameter of air outlet (mm)
150
Grease filter material
Washable aluminium
Odour filter
No
Operating Mode
Convertible
Delay Shut off modes
Required accessories
Optional accessories
Type of lamps used
Total power of the lamps (W)
Grease filter type
Multilayer
Clean filter reminders

Consumption and connection features

Connection Rating (W)
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
Installation typology
Built-in into the cabinet
Universal Product Code
825225916161
Material body
Stainless steel
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (in)
Plug type
Dimensions of the product, with chimney (if exists) (in)
/ x x
Dimensions of the packed product (in)
7.20 x 23.11 x 11.61
Height of the chimney (in)
Vertical rise height
Required distance above cooktop/ranges
Net weight (lbs)
3
Gross weight (lbs)
9
Motor location
N/A
Maximum output recirculating air (CFM)
Diameter of air duct (in) top
Diameter of air duct (in) back
Discharge direction
No-return airflow flap
No
Length electrical supply cord (cm)
200
Dimensions of the product, with chimney (if exists) (mm)
180 x 85.0 x 523.0

GAGGENAU