



Color Variants

VP414110
Stainless steel
Width 38 cm

Included accessories
2 x spatula.

VP414110
Vario Teppan Yaki 400 series
Stainless steel
Width 38 cm

Cooking directly on the hard-chromed metal surface, without any pots or pans
Exact temperature control up to 240 °C
Optimum heat distribution
Solid stainless steel control knob
Precision crafting of 3 mm stainless steel
For surface mounting with a visible edge or for flush mounting
Can be combined perfectly with other Vario appliances of the 400 series

Cooking zones
Usable area W 31 x D 44 cm.

Handling
Control knobs with illuminated ring, cooking zone and temperature markings.
Electronic temperature control from 120 °C to 240 °C.

Features
Two zones, each 1500 W, can be operated together as a complete surface or each half separately. Keeping warm setting.
Even with traces of use, always easy to clean like a cast pan.

Safety
Safety shut-off.

Planning notes
Depending on the type of installation (surface-mounted or flush-mounted, with or without an appliance cover), the specific location of the cut-out and the knob positions may vary.
If installing with the appliance cover VA 440 or filler strip VA 450 take into account the additional space required for the depth.
If combining several appliances with at least one appliance cover, the filler strip VA 450 is required to compensate for the depth of the appliance without the appliance cover.
If combining several Vario appliances of the 400 series, a connection strip VA 420 must be placed between the appliances. Depending on the type of installation, the corresponding connection strip must be provided.
In the cut-out, the installation system requires the side edge to be at least 10 mm for surface mounting and at least 13 mm for flush mounting. Ensure a continuous cut surface of 90°.
The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. Additional instructions for flush mounting:
Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer.
The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining.
The joint width may vary due to size tolerances of the combinations and of the worktop cut-out.


Characteristics
Product name/family
Vario/Domino Teppan Yaki
Built-in / Free-standing
Built-in
Energy input
Electric
Type of control
Electronic
Grill grating material
Required niche size for installation (HxWxD)
72 x 360 x 490
Width of the product (mm)
380
Dimensions of the product (mm)
72 x 380 x 520
Dimensions of the packed product (HxWxD) (mm)
232 x 455 x 593
Net weight (kg)
13.562
Gross weight (kg)
14.8
Residual heat indicator
Separate
Location of control panel
Hob front
Basic surface material
Color of surface
Stainless steel, Stainless steel
Color of frame
Stainless steel
Approval certificates
Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)

Consumption and connection features
Connection Rating (W)
3000
Gas connection rating (W)
Current (A)
16
Voltage (V)
220-240
Frequency (Hz)
60; 50
2020-07-25
Page 1


If installing several appliances in individual cut-outs allow for a division bar of minimum 50 mm between the individual cut-outs.
Built-in control panel to be integrated in the bottom cabinet at drawer level.
Panel thickness 16 - 26 mm.
The drawing "Installation of the control knob" must be observed if the panel is more than 26 mm thick (there must be a recess at the rear).
A minimum lateral clearance of at least 40 mm from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted.
Appliance can be snapped into the worktop from above.
Appliance weight: approx. 14.

Connection
Total connected load 3.0 KW.
Plan a connection cable.


Installation of the control knob; surface mounting




Installation of the control knob; flush installation




Installation with appliance cover/spacer batten;
installation standing proud of surrounding surfaces



Installation with appliance cover/spacer batten;
installation flush with surrounding surfaces




Cross-section





When installing with appliance cover or filler strip, pay attention to the deeper cut-out and the front and rear groove width.

View from above




* with appliance cover or filler strip
(observe the front and rear asymmetrical support,
see separate notes "Installation with appliance
cover/filler strip").

Longitudinal section



* with appliance cover or filler strip.
See separate planning notes.
** 83 mm in the area of the cable clamp (right, centre).




* with appliance cover or filler strip.
See separate planning notes.
** 80 mm in the area of the cable clamp (right, centre).



380	Appliance
3	Connection strip
804	Appliance
1182	Overhang
250	Overhang
1182±2	Cut-out




Without cover




With cover/spacer bottom




380	Appliance
3	Connection strip
110	VL
380	Connection strip
380	Appliance
3	Connection strip
110	VL
380	Connection strip
380	Appliance
1372	Overhang
25	Overhang
1352±2	Cut-out



110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1282	VL
-20	Overhang
1282	Cut-out





110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1981	VL
-20	Overhang
1981	Cut-out



380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
1382	VL
-20	Overhang
1382	Cut-out
+20	Overhang
+8	Slit-on joint
1382	Cut-out with groove



380	Appliance
3	Connection strip
804	Appliance
1183	VL
-20	Overhang
1183	Cut-out
+20	Overhang
+8	Slit-on joint
1183	Cut-out with groove




380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1318	VL
-20	Overhang
1318	Cut-out
+20	Overhang
+8	Slit-on joint
1318	Cut-out with groove


VP414110
Vario Teppan Yaki 400 series
Stainless steel
Width 38 cm
2020-07-25
Page 5




110	VL
3	Connection strip
590	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1312	
-20	Overhang
1292 ⁽²⁾	Cut-out
+20	Overhang
+6	Silicone joint
1318 ⁽²⁾	Cut-out with groove




110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
1981	
-20	Overhang
1961 ¹²	Cut-out
+20	Overhang
+6	Silicone joint
1987 ²	Cut-out with groove






380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
1146	Overhang
1126	Cutout




380	Appliance
3	Connection strip
550	Appliance
3	Connection strip
380	Appliance
1356	Overhang
1336	Cutout




Without cover



With cover/spacer button



380	Appliance
3	Connection strip
380	Appliance
3	Connection strip
380	Appliance
1146	Overhang
-20	Overhang
1126	Cutout
+20	Overhang
-45	Spacer part
1152	Cutout with groove




110	VL
3	Connection strip
590	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1196	Overhang
-20	Overhang
1179	Cutout
+20	Overhang
-45	Spacer part
1200	Cutout with groove




110	VL
3	Connection strip
590	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
1196	Overhang
-20	Overhang
1179	Cutout




380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
1848	Overhang
1848	Cut-out



380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
3	Connection strip
1868	Overhang
20	Overhang
1848	Cut-out
+20	Overhang
+6	Silicone joint
1874	Cut-out with groove



380	Appliance
3	Appliance
110	VL
3	Connection strip
380	Appliance
876	Appliance
20	Overhang
898	Cut-out



380	Appliance
3	Connection strip
110	VL
3	Connection strip
380	Appliance
876	Appliance
20	Overhang
882	Cut-out
+20	Overhang
+6	Silicone joint
882	Cut-out with groove