



#### Color Variants

AC200160  
Stainless steel and glass  
Width 52 cm

#### Optional accessories

AA200510  
Remote control for canopy extractor AC200  
AA210110  
1 activated charcoal filter with high efficient odour reduction due to increased surface. For air recirculation module AA 211 812.

AC200160  
Canopy extractor 200 series  
Stainless steel and glass  
Width 52 cm  
Air extraction / Air recirculation

Can be integrated invisibly in upper cabinet  
Energy-saving, low-noise fan  
Rim extraction with flat and easy-to-clean glass underside  
Dimmable, neutral white LED light for ideal illumination of the whole cooktop  
Air extraction or air recirculation system

#### Output

Performance and noise level, output level 3/Intensive:  
Air output according to EN 61591.  
Sound power level according to EN 60704-3.  
Sound pressure level according to EN 60704-2-13.  
Odour reduction for air recirculation in accordance with EN 61591.  
Air extraction:  
550 / 725 m<sup>3</sup>/h.  
67 / 72 dB (A) re 1 pW.  
53 / 58 dB (A) re 20 µPa.  
Air recirculation:  
550 / 690 m<sup>3</sup>/h.  
72 / 77 dB (A) re 1 pW.  
58 / 63 dB (A) re 20 µPa.  
Odour reduction air recirculation 92 %.

#### Features

3 electronically controlled power levels and 1 intensive mode.  
Remote control is available as a special accessory.  
Interval ventilation, 6 min.  
Run-on function, 6 min.  
Grease filter saturation indicator.  
Metal grease filter, dishwasher-safe.  
Glas filter cover.  
Neutral white LED light (4000 K), dimmable.  
Lamp output 2 x 1 W.  
Illuminance 244 lx.  
Fan technology with highly efficient, brushless DC motor (BLDC).

#### Consumption data

Energy efficiency class A at a range of energy efficiency classes from A++ to E.  
Energy consumption 46.8 kWh/year.  
Ventilation efficiency class A.  
Illumination efficiency class A.  
Grease filter efficiency class D.  
Sound level min. 44 dB / max. 67 dB normal mode.

#### Planning notes

Patented air recirculation module with activated charcoal filter can be installed in the upper cabinet. The activated carbon filter can be changed from the front by simply pulling out the filter drawer.  
The door of the upper cabinet must be fully open in order to change the activated charcoal filter.  
Can be integrated invisibly in upper cabinet.  
Vario cooktops with intensive production of vapours like VR/VP/VF should be placed in the middle beneath the hood (in this case air recirculation is not recommended).  
Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).  
Clearance above electric appliances min. 50 cm.

#### Characteristics

Product name/family  
Color chimney  
Typology  
Traditional  
Approval certificates  
CE, Eurasian, G-Mark, Ukraine  
Length electrical supply cord (cm)  
100  
Required niche size for installation (HxWxD)  
418mm x 496.0mm x 264mm  
Height of the chimney (mm)  
Height of product, without chimney (mm)  
Minimum distance above an electric hob  
500  
Minimum distance above a gas hob  
650  
Net weight (kg)  
10.098  
Type of control  
Electronic  
Number of speed settings  
Maximum output air extraction (m<sup>3</sup>/h)  
550  
Boost position output recirculating (m<sup>3</sup>/h)  
690.0  
Maximum output recirculating air (m<sup>3</sup>/h)  
h)  
Boost position air extraction (m<sup>3</sup>/h)  
725  
Number of lights  
2  
Noise level (dB)  
67  
Diameter of air outlet (mm)  
120 / 150  
Grease filter material  
Washable aluminium  
EAN code  
4242006257460

#### Consumption and connection features

Connection Rating (W)  
272  
Current (A)  
3  
Voltage (V)  
220-240  
Frequency (Hz)  
50  
Plug type  
Gardy plug w/ earthing  
Installation typology  
Built-in  
2020-01-30  
Page 1

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

#### Connection

Total connected load 272 W.  
Connecting cable 1.0 m with plug.

