



AR403122

AA400510:  
Window contact switch with cable

## Remote fan unit 400 series

### AR403122

- Efficient BLDC technology
  - Compact and space-saving installation in a 10 cm high plinth
  - Power levels depend on the motorless appliances, see table on page XX.
  - 3 electronically controlled power levels and one intensive mode.
  - Fan technology with highly efficient, brushless DC motor (BLDC).
  - Efficient BLDC technology
- Compact and space-saving installation in a 10 cm high plinth

#### Output

Power levels depend on the motorless appliances, see table on page XX.

#### Features

3 electronically controlled power levels and one intensive mode.

Fan technology with highly efficient, brushless DC motor (BLDC).

Steel housing, zinc-plated.

Pipe connection pieces on intake side: 1 x NW 150 round.

Pipe connection pieces on output side: 1x NW 150 flat duct.

Retaining bracket for installation on the ceiling or side of a cupboard enclosed.

#### Performance

Connection to the respective appliances via network cable.

Installation in the plinth with cut-out for the air ducting in the furniture base.

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

#### Connection

Total connected load 180 W.

Connecting cable 1.8 m, pluggable.

Network cable 2 m.

