



A

Color Variants

BS475101

Included accessories

1 x outlet hose 3m.
1 x STS tray-GN2/3-punched-40 mm deep.
1 x STS tray-GN2/3-unpunched-40 mm deep.
1 x grid.
1 x pluggable meat probe.
1 x water inlet hose 3m.
4 x cleaning cartridge.

Optional accessories

CLS10040
Cleaning cartridges, set of 4
GN114130
Gastronorm insert, stainless steel, GN 1/3
GN114230
Gastronorm insert, stainless steel, GN 2/3
GN144130
Gastronorm insert, non-stick, GN 1/3
GN144230
Gastronorm insert, non-stick, GN 2/3
GN154130
Gastronorm insert, non-stick, GN 1/3
GN154230
Gastronorm insert, non-stick, GN 2/3
GN340230
Gastronorm roaster in cast aluminium.
GN410130
Gastronorm lid, stainless steel, GN 1/3
GN410230
Gastronorm lid, stainless steel, GN 2/3

Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in

Door opening

Lateral

Required niche size for installation

(HxWxD)

450-450 x 560-560 x 550

Dimensions

Dimensions of the packed product

(HxWxD) (mm)

575 x 660 x 690

Control Panel Material

Door Material

Glass

Net weight (kg)

45.496

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

EAN code

4242006249809

Electrical connection rating (W)

Current (A)

12

Voltage (V)

220-240

Frequency (Hz)

50

Plug type

no plug

Approval certificates

Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Number of cavities (2010/30/EC)

1

Usable volume (of cavity) - NEW

(2010/30/EC)

44

Energy efficiency rating

A

Energy consumption per cycle

conventional (2010/30/EC)

Energy consumption gas oven per cycle

conventional (2010/30/EC)

Energy consumption per cycle forced

air convection (2010/30/EC)

0.70

Energy consumption gas oven per cycle

forced air convection (2010/30/EC)

Energy efficiency index (2010/30/EC)

95.9

Consumption and connection features

2021-06-20

Page 1