



#### Color Variants

BSP250101

#### Included accessories

1 x grid.  
1 x pluggable meat probe.  
1 x STS tray.  
punched.  
40 mm deep.  
1 x STS tray.  
unpunched.

#### Optional accessories

BA010301

Flush installation  
Water tank for fresh and waste water  
Large cavity  
LED light source  
External steam generation  
Steaming without pressure  
Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%  
Sous-vide cooking with accurate temperature regulation  
Automatic programmes  
Core temperature probe with estimation of cooking time  
Hot air fan rotates in both directions for ideal heat distribution  
TFT touch display  
Panel-free appliance with surface control module  
Electronic temperature control from 30 °C to 230 °C  
Net volume 50 litres

#### Heating methods

Hot air + 100 % humidity.  
Hot air + 80 % humidity.  
Hot air + 60 % humidity.  
Hot air + 30 % humidity.  
Hot air + 0 % humidity.  
Low temperature cooking.  
Sous-vide cooking.  
Full surface grill level 1 + humidity.  
Full surface grill level 2 + humidity.  
Full surface grill + circulated air.  
Dough proofing.  
Defrosting.  
Regenerating.

#### Capacity

Rotary knob and TFT touch display operation.  
Clear text display.  
Option to save individual recipes (incl. core temperature probe).  
Personalisation of automatic programmes.  
Information key with use indicators.  
Side-opening door opens up to 110° angle.

#### Features

2 removable 1.7 litre water tanks.  
Water level warning.  
Three-point core temperature probe with automatic shut-off and estimation of cooking time.  
Automatic programmes.  
Actual temperature display.  
Automatic boiling point detection.  
LED light on the side.  
Hygienic stainless steel cooking interior.  
3 tray levels.  
Home network integration for digital services (Home Connect) either via cable connection LAN or wireless via WiFi.  
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

#### Safety

Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

#### Cleaning

Cleaning aid.

#### Characteristics

Color / Material Front

Anthracite

Built-in / Free-standing

Built-in

Door opening

Lateral

Integrated Cleaning system

No

Control Panel Material

without panel

Door Material

Glass

Dimensions

455x590x540

Dimensions of the packed product

(HxWxD)

590x660x700

Required niche size for installation

(HxWxD)

450-450 x 560-560 x 550

Cavity dimensions

248 x 501 x 406

Usable volume (of cavity) - NEW

(2010/30/EC)

50

Number of interior lights

1

Net weight

45.1

Gross weight

47.3

EAN code

4242006278120

Connection Rating

3150

Fuse protection

16

Voltage

220-240

Frequency

50

Length electrical supply cord

175

#### Consumption and connection features

2025-12-12

Page 1

Descaling programme for the steam generator.

Drying function.

Automatic drying of the cavity at the end of the cooking process.

Water tank, dishwasher-safe.

Grease filter, dishwasher-safe.

Strainer filter, removable.

#### Performance

Door hinge not reversible.

No other electrical appliances should be installed above the BS.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

The mains socket needs to be planned outside the built-in niche.

The LAN port can be found at the back on the lower left side.

#### Connection

Total connected load 3.1 KW.

Connecting cable 1.8 m with plug.

Plan a LAN cable.

Power consumption standby/display on 0.8 W.

Power consumption standby/display off 0.5 W.

Power consumption standby/network 1.8 W.

Time auto-standby/display on 20 min.

Time auto-standby/display off 20 min.

Time auto-standby/network 20 min.

Please check the user manual for how to switch off the WiFi module.

# GAGGENAU

