

Color Variants	
CX482100	
Frameless	
Width 80 cm	

Included accessories

1 x wireless temperature sensor for cooktop.

Optional accessories CA060300 Cooking sensor for temperature regulation within pots GN232110 Teppan Yaki plate made of multi ply material.

GN232230 Teppan Yaki plate made of multi ply material,

CX482100 Full surface induction cooktop 400 series Frameless Width 80 cm

One single big cooking surface Free positioning of cookware All sizes and formats of cookware can be used TFT touch display for an intuitive control of all functions Cooking sensor function for temperature control in pots Professional cooking functions Max. power output for big cookware of up to 5.5 KW Frameless for flush mounting

Cooking zones

One unique cooking surface of 2750 cm². Up to 5 items of cookware can be

placed simultaneously on the cooktop.

Handling

Easy to use colour graphic TFT touch display with use indications. Electronic power control in 17 cooking power levels.

Features

Cooking sensor function. Professional cooking function. Dynamic cooking function. Teppan Yaki function. Booster function for pots. Booster function for pans. Keep warm function. Individual pot detection. Cooking timer for each cooking position. Stopwatch. Short-term timer. Information key with use indicators. Power management. Cooktop-based ventilation control (with suitable hood). Home network integration for digital services (Home Connect) wireless via WiFi. The use of the Home Connect functionality depends on the Home

available in every country. For further information please check: homeconnect.com.

Safety

Main switch. Residual heat indication. Child lock. Safety shut-off. Pause function.

Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of sandwich bottom cookware is recommended. The wok pan WP 400 001 cannot be used with this appliance. Installation is possible in worktops made of stone, synthetics or solid wood. Heat resistance and watertight sealing of the cut edges must be observed. Concerning other materials please consult the worktop manufacturer. The bearing capacity and stability, in the case of thin worktops in particular, must be supported using suitable substructures. Take into account the appliance weight and additional loads. The groove must be continuous and even, so that uniform placing of the appliance on the gasket is ensured. Do not use discontinuous lining. Appliance must be fixed from underneath.

Characteristics

Product name/family Cooking zone ceramic Construction type Built-in Energy input Electric Total number of positions that can be used at the same time

Type of control setting devices Required niche size for installation (HxWxD) Width of the appliance

793 Dimensions 76 x 793 x 513 Dimensions of the packed product (HxWxD) (mm) 152 x 951 x 636 Net weight (kg) 27.200 Gross weight (kg) 29.1 Residual heat indicator Separate Location of control panel Hob front Type of external control possibility Basic surface material Color of surface anthracite Color of frame Approval certificates AENOR, CE Length electrical supply cord (cm) 150 EAN code 4242006268794 Electrical connection rating (W) 7400 Gas connection rating (W) Current (A) Voltage (V) 220-240 Frequency (Hz) 60: 50

Consumption and connection features 2021-07-05 Page 1 Joint width may vary due to dimensional tolerances of the glass ceramic cooktop and the worktop cut-out. Appliance weight: approx. 27. kg

Connection


Total connected load 7.4 KW. Connecting cable 1.5 m without plug. Power consumption standby/display off 0.5 W. Power consumption standby/network 2.0 W.

Please check the user manual for how to switch off the WiFi module.



CX482100
Full surface induction cooktop 400
series
Frameless
Width 80 cm
2021-07-05
Page 2








•







View from above



