



DV461110

Built-in vacuum drawer 400 series
60 x 14 cm, Stainless steel behind glass
DV461110

Integrable in 14 cm high niche
Hygienic stainless steel vacuuming chamber,
applicable height up to 80 mm
3 vacuuming levels for vacuuming in the
chamber, max. 99%
3 vacuuming levels for vacuuming outside the
chamber, max. 90%
Automatic connection recognition for vacuuming
outside the chamber
Handleless drawer
Cushioned closing system

Application

Vacuuming for sous-vide cooking.
Vacuuming for fast marinating and flavouring.
Vacuuming for extended storage.
Vacuuming of vacuuming containers outside the
chamber.
Vacuuming of liquids in bottles outside the
chamber.

Capacity

Touch key operation.
Recessed grip at the front bottom of the drawer.

Features

Net volume 7 litres.
Capacity load max. 10 kg.
Maximum size of vacuuming bags W 240 mm x L
350 mm.
3 heat-sealing levels for different strengths of
bag material.
Sealing bar, non-stick coating, removable.
Safety glass cover, opens automatically after
vacuuming.
Raised vacuuming platform, 44 mm, deployable.
Utility space in vacuuming chamber, W 210 mm
x L 275 mm.
Membrane for avoiding reflow of liquids during
vacuuming outside the chamber.
Drying programme for vacuuming pump.
Warning function.

Performance

The panel surface of the appliance extends 47
mm from the furniture cavity.
Installation of BS/BM/CM directly above DV in
59 cm niche without intermediate floor.
Built-in under worktop or in single niche.
The socket can be planned behind the
appliance.

Connection

Total connected load 0.32 KW.

Side view of DV 461 below BS, BM, CM

