



RB287503

GN114130:

GN insert unperf, st. steel, GN1/3, 40mm

GN114230:

GN insert unperf, st. steel, GN2/3, 40mm

GN144130:

GN insert 1/3 unperf, non-stick, 40mm

GN144230:

GN insert 2/3 unperf, non-stick, 40mm

GN410130:

GN lid stainless steel 1/3

GN410230:

GN lid stainless steel 2/3

RA430100:

Storage container with lid, anthracite

Vario Built-in fridge-freezer with freezer at bottom 200 Series

177.2 x 55.6 cm, soft close flat hinge

RB287503

Enlarged interior with 264 litre net volume through compressor relocation
Cushioned door closing system allowing a soft and controlled door closure
Smooth running fully extendable telescopic pull-out racks and a cushioned closing system allow a soft and controlled closure of the drawers

Capacity

Electronic temperature control with temperature display.

Touch keys.

Technical Information

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Cushioned door closing system from 20° door opening angle, integrated in door hinge.

Open-door and malfunction alarm.

Cooling

Fast cooling.

Temperature adjustable from +2 °C to +8 °C.

3 safety glass shelves, 2 of which are height adjustable and 1 fully extendable.

Wine and champagne rack for 4 bottles, can be completely folded away.

Fixture for storing glass tray.

1 large door rack with aluminium profile for bottles with flexible bottle holder.

2 door racks with aluminium profile.

1 vegetable drawer.

Bright interior lighting with integrated glare-free side light elements.

Stepped shelf in aluminium for optimum use of interior and for storing GN inserts.

Possible combinations: 1 x 1/3 GN 2 x 1/3 GN 3 x 1/3 GN 1 x 2/3 GN 1 x 2/3 GN and 1 x 1/3 GN

Net fridge capacity total: 189 l litres.

Freezing

No-frost technology with fast freezing.

Temperature adjustable from -14 °C to -24 °C.

3.5 Energy star rating

Freezing capacity 15 kg/24 h.

Storage time after a malfunction 16 h.

3 freezer drawers, 1 of which extra large.

Consumption Rates

4.5 Energy Star Rating

Energy consumption 330 kWh

Noise level 39 dB (re 1 pW).

Performance

Flat hinge.

Door hinge right, reversible.

Door opening angle of 115°, fixable at 90°.

Appliance plinth recess 90 mm.

Max. door panel weight:

Upper door 22 kg. Lower door 22 kg.

Necessary gap between furniture door panels 4 mm.

Connection

Total connected load 0.120 KW.

Connecting cable 1.9 m with plug.

