



RC289503

2 x egg tray
1 x wine and champagne rack
1 x glass tray
1 x gastronorm insert 1/3 stainless steel
1 x gastronorm lid 1/3 stainless steel

GN114130:
GN insert unperf, st. steel, GN1/3, 40mm

GN114230:
GN insert unperf, st. steel, GN2/3, 40mm

GN144130:
GN insert 1/3 unperf, non-stick, 40mm

GN144230:
GN insert 2/3 unperf, non-stick, 40mm

GN410130:
GN lid stainless steel 1/3

GN410230:
GN lid stainless steel 2/3

RA430100:
Storage container with lid, anthracite

Vario built-in fridge 200 Series 177.5 x 56 cm, soft close flat hinge RC289503

Enlarged interior with 302 litre net volume through compressor relocation
3 climate zones incl. three fresh cooling drawers close to 0 °C
Combines with freezer RF 287 (Side-by-side integration)
Cushioned door closing system allowing a soft and controlled door closure
Smooth running fully extendable telescopic pull-out racks and a cushioned closing system allow a soft and controlled closure of the drawers

Capacity

Electronic temperature control with temperature display.
Touch keys.

Technical Information

Dynamic cold air distribution.
Cushioned door closing system from 20° door opening angle, integrated in door hinge.
Open-door alarm.

Cooling

Fast cooling.
Automatic defrosting with defrost water evaporation.
Temperature adjustable from +2 °C to +8 °C.
2 full depth safety glass shelves, fully extendable.
4 safety glass shelves, 2 of which are fully extendable and 2 height adjustable.
Wine and champagne rack for 4 bottles, can be completely folded away.
Fixture for storing glass tray.
1 large door rack with aluminium profile for bottles with flexible bottle holder.
2 door racks with aluminium profile.
Bright interior lighting with integrated glare-free side light elements.
Stepped shelf in aluminium for optimum use of interior and for storing GN inserts.
Possible combinations: 1 x 1/3 GN 2 x 1/3 GN 3 x 1/3 GN 1 x 2/3 GN 1 x 2/3 GN and 1 x 1/3 GN

Fresh cooling close to 0 °C

Ideal for meat, fish and poultry.
1 fully extendable fresh cooling drawer close to 0 °C, humidity optimized.
Ideal for fruit and vegetables.
Total volume without *
Activated charcoal air filter.

Consumption Rates

4.5 Energy Star Rating
Energy consumption 225 kWh
Noise level 39 dB (re 1 pW).

Performance

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, fixable at 90°.
Appliance plinth recess 90 mm.
Max. door panel weight 22 kg.

Connection

Total connected load 0.120 KW.
Connecting cable 1.9 m with plug.

