

**Color Variants** 

RW282261

Fully integrated, with glass door Niche width 56 cm, Niche height 177.2

Installation Accessories

RA425110

Handle bar, stainless steel, long

#### RW282261

Wine climate cabinet

Fully integrated, with glass door

Niche width 56 cm, Niche height 177.2

2 independently controllable climate

Consistent temperatures with exact control from +5 °C to +20 °C Humidity control

Extendable bottle trays in beech and aluminium

Presentation light option Low-vibration operation Capacity 80 bottles

#### Handling

Electronic temperature control with digital display

Touch kevs.

Presentation light option in each climate zone, dimmable.

Interior lighting with automatic dimming with opening and closing of door.

### Technical Features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation.

Cushioned door closing system integrated in door hinge

1 activated charcoal air filter for both climate zones.

UV-protection.

Open-door and malfunction alarm. Child lock.

#### Features

Capacity 80 bottles (based on 0.75/I standard bottles).

10 bottle trays, 8 of which are extendable.

Storage of magnum bottles possible. LED lighting.

Net volume 254 litres.

## Consumption data

Energy efficiency class A at a range of energy efficiency classes from A+++ to

Energy consumption 163 kWh/year. Noise level 35 dB (re 1 pW).

## Planning notes

Flat hinge

Door hinge right, reversible.

Height-adjustable feet.

Door opening angle of 115°, fixable at 90°

Max. door panel weight 20 kg. Door panel thickness min. 16 mm/ max.22mm.

The mains socket needs to be planned outside the built-in niche.

For a side-by-side installation every appliance must be planned in its own niche.

When combining the wine climate cabinet with cooling appliances other than a second wine climate cabinet, these must have side heating to avoid condensation. Without side heating a clearance of min. 150 mm is to be kept between the appliances

No transport/operation above 1.500 m sea level.

## Connection

Total connected load 0.130 KW. Connecting cable 2.8 m with plug.

#### Characteristics

Built-in / Free-standing

Built-in

Door panel options Possible but accessory

Height (mm)

Width of the appliance

1770 557

Depth of the product

Required niche size for installation (HxWxD)

1772.0 x 560 x 550

Net weight (kg)

90,000

Connection Rating (W)

Current (A)

Voltage (V) 220-240

Frequency (Hz)

Approval certificates

CE, VDE

Length electrical supply cord (cm)

Plug type

Gardy plug w/ earthing

Energy consumption (kWh/d) winecooler

Energy consumption per Year (kWh/a)

Total unit gross capacity (I)

Number of compressors

Number of independent cooling systems

Interior ventilator

Reversible Door Hinge

Interior light switch

Number of temperature zones

Range of temperature (°C)

Economy setting

Carbon Air Filter

Presenter Lighting

**Presenter Shelf** 

Type of Glass Door

3 glass panels, UV-filter

Number of adjustable shelves

Number of shelves

Bottles per Shelf

Material of the shelves

Type of Light

Interior ventilator

Brand

Gaggenau

Product name / Commercial code

RW282261

Product category

Energy efficiency rating

Energy consumption annual (kWh/ annum) - NEW (2010/30/EC) 163.00

Capacity in 0.75l (bordeaux bottles)

Climate class

SN-ST

Noise level (dB)

**Universal Product Code** Color / Material body

Door panel options

Possible but accessory


Installation typology Half-integrated


Noise level (dB)




RW282261 Wine climate cabinet Fully integrated, with glass door Niche width 56 cm, Niche height 177.2 cm

2021-05-04 Page 2







# **GAGGENAU**