



Color Variants

RB472705
With fresh cooling close to 32 °F
Fully integrated, panel ready

Included accessories

1 x egg box with lid.
1 x ice cube scoop.

Optional accessories

RA430100
Storage container with transparent lid, anthracite.
RA450022

Installation Accessories

RA421715
Stainless steel door panel with handles
RA423340
RA425110
Long stainless steel door handle
RA425710
Short stainless steel door handle
RA428715
Stainless steel door panels, handleless
RA460000
Installation kit for side-by-side installation (for connecting any two columns)
RA460012
RA460030
Connecting element for vertically split fronts (for fridge-freezer combination with one door)
RA464713
Ventilation grill, stainless steel

RB472705
Vario fridge-freezer combination 400 series
With fresh cooling close to 32 °F
Fully integrated, panel ready
Niche width 30" (76.2 cm)
Cooling section with one door and one fully extendable freezing drawer



Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots
Opening assist for door with two options:
1. Push-to-open function for integration into handleless furniture front
2. Pull-to-open function to facilitate opening the door using a handle
Flat stainless steel inner door, full-length
Almost invisible rail system for shelves and door racks for flexible positioning
Solid anthracite aluminium door racks
1 fresh cooling drawer close to 32 °F with manually adjustable temperature and one fresh cooling drawer with manually adjustable humidity
Integrated automatic ice maker with fixed water connection
Fully extendable freezer drawer with practical divider in anthracite
TFT touch display
Net volume 16 ft3 cu.ft. (452) litres
Energy Star certified

Operation

TFT touch display operation.
Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
Automatic defrosting with defrost water evaporation.
Cushioned door closing system.
Activated charcoal air filter.
Sabbath mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction warning system.
Home network integration for digital services (Home Connect) wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling compartment

No-Frost technology with fast cooling.
Temperature adjustable from 35 °F to 46 °F.
Flat door rail system with fully flexible positioning of door racks.
3 height adjustable door bins, one of which is a large gallon door bin.
Net volume 324 l liters.

Fresh cooling close to 32 °F

1 fully extendable fresh cooling drawer close to 32 °F with transparent front, illuminated.
Cushioned closing system.
Temperature can be adjusted manually.
Ideal for meat, fish and poultry.
Net volume 0 litres.

Temperature controlled drawer

1 fully extendable fresh cooling drawer with transparent front, illuminated.
Cushioned closing system.
Humidity can be adjusted manually.
Ideal for fruit and vegetables.

Freezer compartment

No-frost technology with fast freezing at -22 °F.

Product Features	
UPC code	825225960997
Color / Material housing	
Variant color	Not applicable
Panel ready	Not possible
Silence level (dBA)	42
Watts (W)	350
Current (A)	10
Volts (V)	110-120
Frequency (Hz)	60
Total annual energy consumption (kWh)	469.9
ENERGY STAR®	Yes
Approval certificates	CSA
Power Cord Length	118,1"
Required cutout size (HxWxD) (in)	84" x 30" x 24 3/4"
Appliance Width (in)	29 3/4"
Height (in)	83 3/4 "
Depth (in)	24"
Capacity in 0.75l (bordeaux bottles)	
Total unit gross capacity (cu. ft.) - AHAM	16.0
Product packaging dimensions (HxWxD) (in)	89.01 x 32.51 x 29.56
Refrigerator Gross capacity (cu. ft.)	11.5
Freezer Gross capacity (cu ft)	4
Net weight (lbs)	403.000
Gross weight (lbs)	441.000
SKU	RB472705

Consumption and connection features

2021-06-20
Page 1

Temperature adjustable from 3 °F to -11 °F.
4-star freezer compartment.
Freezing capacity 5.8 kg/24 h.
Interior lighting with 2 LED light spots, warm white light.

Ice dispenser

Integrated automatic ice maker in the freezer compartment, with fixed water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Saturation indicator shown in TFT touch display.
Ice maker can be switched off independently.
Ice cube production approx. 2.9 lb (1.3 kg)/24 h.
Removable ice storage container with approx. 6.6 lbs. (3 kg) capacity.

Consumption data

Energy consumption 469.86 kWh/year.
Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, fixable at 90°.
Max. door panel weight:
Door 103 lbs (47 kg).
Drawer 22 lbs (10 kg).
Shut-off valve for water connection must be planned next to the appliance and always be accessible.
If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

Rating

Total rating 1.079 kWh/24 h.
Total Amps: 10 A.
Connecting cable 118" (3.0 m), detachable.
Cold water connection required.
Electrical location 6" above ground in lower left corner of unit.
Supply hose 51,1 INCH (1.3 m) with 1/4" male compression fitting (standard icemaker connector).
Water pressure 29 to 116 psi.

RB472705
Vario fridge-freezer combination 400 series
With fresh cooling close to 32 °F
Fully integrated, panel ready
Niche width 30" (76.2 cm)
Cooling section with one door and one fully extendable freezing drawer
2021-06-20
Page 2

