



AI240190
Island hood 200 series
Stainless steel with stainless steel control panel
Width 90 cm
Air extraction / Air recirculation
Delivery with mounting kit and chimney

Timeless, elegant design
Highly efficient extraction of cooking vapours
Energy-saving, low-noise fan
Patented filter technology with high grease absorption
Rim extraction filter with flat and easy-to-clean stainless steel underside
Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours
Air extraction or air recirculation system
Air recirculation module with activated charcoal filter: quiet and highly efficient air recirculation solution with odour reduction as in air extraction mode and long replacement intervals

Output

Performance and noise level, output level 3/Intensive:
 Air output according to EN 61591.
 Sound power level according to EN 60704-3.
 Sound pressure level according to EN 60704-2-13.
 Odour reduction for air recirculation in accordance with EN 61591.
 Air extraction:
 620 / 850 m³/h.
 62 / 69 dB (A) re 1 pW.
 48 / 55 dB (A) re 20 µPa.
 Air recirculation:
 480 / 570 m³/h.
 68 / 72 dB (A) re 1 pW.
 54 / 58 dB (A) re 20 µPa.
 Odour reduction air recirculation 95%.

Features

3 electronically controlled power levels and 1 intensive mode.
 Automatic function with sensor-controlled run-on function.
 Grease filter saturation indicator.
 Patented rim extraction filter, dishwasher-safe.
 Fan technology with highly efficient, brushless DC motor (BLDC).
 Airflow-optimised interior for efficient air circulation.
 The package includes an one-way flap.

Planning notes

The package includes the mounting kit and the two-part chimney with the dimensions from 674 mm to 854 mm. Individual planning solutions can be implemented using the special accessory chimney extension AD 200 326 in combination with extension for mounting kit AD 223 346.
 Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm).
 Clearance above electric appliances min. 55 cm.
 The air recirculation module with activated charcoal filter can be installed on the inner chimney.
 When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection

Total connected load 280 W.
 Connecting cable 1.3 m with plug.

Consumption data

Energy consumption 52.5 kwh/year.

Characteristics

Product name/family
Color chimney
Typology
 Chimney
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
 130
Required niche size for installation (HxWxD)
Height of the chimney (mm)
 674-854
Height of product, without chimney (mm)
 70
Net weight (kg)
 33.767
Type of control
 Electronic
Number of speed settings
Maximum output air extraction (m3/h)
 620
Boost position output recirculating (m3/h)
 570.0
Maximum output recirculating air (m3/h)
Boost position air extraction (m³/h)
 850
Number of lights
 4
Noise level (dB(A) re 1 pW)
 62
Diameter of air outlet (mm)
 150 / 120
Grease filter material
 Washable stainless steel
Odour filter
 No
Operating Mode
 Convertible
Delay Shut off modes
Required accessories
Optional accessories
 AA200110, AA200816
Type of lamps used
 LED
Total power of the lamps (W)
 20
Grease filter type
 Multilayer
Clean filter reminders

Consumption and connection features
Connection Rating (W)
 280
Current (A)
 10
Voltage (V)
 220-240
Frequency (Hz)
 50; 60
Plug type
 Gardy plug w/ earthing
Installation typology
 Island
Universal Product Code
 825225913627
Material body
 Stainless steel
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (in)
Plug type
 Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in)
 / x x
Dimensions of the packed product (in)
 32.87 x 24.01 x 40.74
Height of the chimney (in)
Vertical rise height
Required distance above cooktop/ranges
Net weight (lbs)
 74
Gross weight (lbs)
 94

Ventilation efficiency class A.
 Illumination efficiency class A.
 Grease filter efficiency class B.
 Sound level min. 40 dB / max. 62 dB normal mode.
 Illuminance 770 lx.
 Lamp output 4 x LED 6medium power 5W stripe.
 Dimmable, neutral white LED light for ideal illumination of the whole cooktop
 Neutral white LED light (3600 K), continuously dimmable.
 Energy efficiency class A at a range of energy efficiency classes from A++ to E.

Color Variants

AI240190
 Stainless steel with stainless steel control panel
 Width 90 cm

Optional accessories

AA200110
 Active charcoal filter for retrofitting recirculation module AA 200 812/816
 AA200816
 Recirculation module with activated charcoal filter

Installation Accessories

AD200326
 Stainless steel chimney extension
 Length: 1100 mm
 AD220396
 Ceiling collar for air ducts
 Stainless steel