



AR403121

## Remote fan unit 200 series

### AR403121

- Powerful remote fan unit to combine with motorless downdraft ventilation VL 040/041 200 series
- Compact and space-saving installation in a 10 cm high plinth
- Performance output level 3/4:
- Air output according to EN 61591. Sound power and sound pressure depending on built-in situation.
- Air extraction:
  - 764 / 908 m<sup>3</sup>/h.
- Power levels depend on the motorless appliances, see table on page XX.
- Powerful remote fan unit to combine with motorless downdraft ventilation VL 040/041 200 series

Compact and space-saving installation in a 10 cm high plinth

#### Output

Performance output level 3/4:

Air output according to EN 61591. Sound power and sound pressure depending on built-in situation.

Air extraction:

764 / 908 m<sup>3</sup>/h.

Power levels depend on the motorless appliances, see table on page XX.

#### Features

4 power levels.

Steel housing, zinc-plated.

Pipe connection pieces on intake side: 1 x NW 150 round.

Pipe connection pieces on output side: 1x NW 150 flat duct.

Retaining bracket for installation on the ceiling or side of a cupboard enclosed.

#### Planning notes

Remote fan unit in combination with motorless downdraft ventilation VL 040/041.

Installation in the plinth with cut-out for the air ducting in the furniture base.

Connection of 2 x VL with an air collector box (AD 754 048, AD 854 048).

When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

#### Connection

Fan output 200 W.

Connecting cable 1.8 m with plug.

