



**AW240120**  
**Wall-mounted hood 200 series**  
**Stainless steel with stainless steel control panel**  
**Width 120 cm**  
**Air extraction / Air recirculation**

**Timeless, elegant design**  
**Highly efficient extraction of cooking vapours**  
**Energy-saving, low-noise fan**  
**Patented filter technology with high grease absorption**  
**Rim extraction filter with flat and easy-to-clean stainless steel underside**  
**Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours**  
**Air extraction or air recirculation system**  
**Air recirculation module with activated charcoal filter: quiet and highly efficient air recirculation solution with odour reduction as in air extraction mode and long replacement intervals**

**Output**  
 Performance and noise level, output level 3/Intensive:  
 Air output according to EN 61591.  
 Sound power level according to EN 60704-3.  
 Sound pressure level according to EN 60704-2-13.  
 Odour reduction for air recirculation in accordance with EN 61591.  
 Air extraction:  
 600 / 800 m<sup>3</sup>/h.  
 64 / 70 dB (A) re 1 pW.  
 50 / 56 dB (A) re 20 µPa.  
 Air recirculation:  
 400 / 460 m<sup>3</sup>/h.  
 65 / 68 dB (A) re 1 pW.  
 51 / 54 dB (A) re 20 µPa.  
 Odour reduction air recirculation 95%.

**Features**  
 3 electronically controlled power levels and 1 intensive mode.  
 Automatic function with sensor-controlled run-on function.  
 Grease filter saturation indicator.  
 Patented rim extraction filter, dishwasher-safe.  
 Fan technology with highly efficient, brushless DC motor (BLDC).  
 Airflow-optimised interior for efficient air circulation.  
 Easy mounting system for simple installation and alignment.  
 The package includes an one-way flap.

**Planning notes**  
 The package includes the two-part chimney with the dimensions from 582 mm to 884 mm. Individual planning solutions can be implemented using the special accessory chimney extension AD 200 322 or by shortening the lower edge of the inner chimney. Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm). Clearance above electric appliances min. 55 cm.  
 The air recirculation module with activated charcoal filter can be installed on the external chimney or inner chimney.  
 When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

**Connection**  
 Total connected load 280 W.

**Characteristics**  
**Product name/family**  
**Color chimney**  
**Typology**  
 Chimney  
**Approval certificates**  
 CE, Eurasian, G-Mark, Ukraine, VDE  
**Length electrical supply cord (cm)**  
 130  
**Required niche size for installation (HxWxD)**  
**Height of the chimney (mm)**  
 582-884  
**Height of product, without chimney (mm)**  
 70  
**Net weight (kg)**  
 25.800  
**Type of control**  
 Electronic  
**Number of speed settings**  
**Maximum output air extraction (m3/h)**  
 634  
**Boost position output recirculating (m3/h)**  
 460.0  
**Maximum output recirculating air (m3/h)**  
**Boost position air extraction (m<sup>3</sup>/h)**  
 800  
**Number of lights**  
 4  
**Noise level (dB(A) re 1 pW)**  
 64  
**Diameter of air outlet (mm)**  
 120 / 150  
**Grease filter material**  
 Washable stainless steel  
**Odour filter**  
 No  
**Operating Mode**  
 Convertible  
**Delay Shut off modes**  
**Required accessories**  
**Optional accessories**  
 AA200110, AA200812  
**Type of lamps used**  
 LED  
**Total power of the lamps (W)**  
 20  
**Grease filter type**  
 Multilayer  
**Clean filter reminders**  
  
**Consumption and connection features**  
**Connection Rating (W)**  
 280  
**Current (A)**  
 10  
**Voltage (V)**  
 220-240  
**Frequency (Hz)**  
 50; 60  
**Plug type**  
 Gardy plug w/ earthing  
**Installation typology**  
 Wall-mounted  
**Universal Product Code**  
 825225913870  
**Material body**  
 Stainless steel  
**Approval certificates**  
 CE, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (in)**  
**Plug type**  
 Gardy plug w/ earthing  
**Dimensions of the product, with chimney (if exists) (in)**  
 / x x  
**Dimensions of the packed product (in)**  
 22.83 x 24.01 x 51.57  
**Height of the chimney (in)**  
**Vertical rise height**  
**Required distance above cooktop/ranges**  
**Net weight (lbs)**  
 57  
**Gross weight (lbs)**  
 81  
**Motor location**  
 Integrated motor in hood chimney

Connecting cable 1.3 m with plug.

**Consumption data**  
 Energy consumption 45.5 kwh/year.  
 Ventilation efficiency class A.  
 Illumination efficiency class A.  
 Grease filter efficiency class B.  
 Sound level min. 43 dB / max. 64 dB normal mode.  
 Illuminance 929 lx.  
 Lamp output 4 x LED 6medium power 5W stripe.  
 Dimmable, neutral white LED light for ideal illumination of the whole cooktop  
 Neutral white LED light (3600 K), continuously dimmable.  
 Energy efficiency class A at a range of energy efficiency classes from A++ to E.

**Color Variants**  
**AW240120**  
 Stainless steel with stainless steel control panel  
 Width 120 cm

**Optional accessories**  
**AA200110**  
 Active charcoal filter for retrofitting recirculation module AA 200 812/816  
**AA200812**  
 Recirculation module with activated charcoal filter

**Installation Accessories**  
**AD200322**  
 Stainless steel chimney extension  
 Length: 1000 mm  
**AD200392**  
 Ceiling collar for air ducts  
 Stainless steel