



AW240190
Wall-mounted hood 200 series
Stainless steel with stainless steel control panel
Width 90 cm
Air extraction / Air recirculation

Timeless, elegant design
Highly efficient extraction of cooking vapours
Energy-saving, low-noise fan
Patented filter technology with high grease absorption
Rim extraction filter with flat and easy-to-clean stainless steel underside
Function for automatic, sensor-controlled power adjustment depending on the build-up of cooking vapours
Air extraction or air recirculation system
Air recirculation module with activated charcoal filter: quiet and highly efficient air recirculation solution with odour reduction as in air extraction mode and long replacement intervals

Output
 Performance and noise level, output level 3/Intensive:
 Air output according to EN 61591.
 Sound power level according to EN 60704-3.
 Sound pressure level according to EN 60704-2-13.
 Odour reduction for air recirculation in accordance with EN 61591.
 Air extraction:
 610 / 810 m³/h.
 66 / 72 dB (A) re 1 pW.
 52 / 58 dB (A) re 20 µPa.
 Air recirculation:
 450 / 530 m³/h.
 70 / 74 dB (A) re 1 pW.
 56 / 60 dB (A) re 20 µPa.
 Odour reduction air recirculation 95%.

Features
 3 electronically controlled power levels and 1 intensive mode.
 Automatic function with sensor-controlled run-on function.
 Grease filter saturation indicator.
 Patented rim extraction filter, dishwasher-safe.
 Fan technology with highly efficient, brushless DC motor (BLDC).
 Airflow-optimised interior for efficient air circulation.
 Easy mounting system for simple installation and alignment.
 The package includes a one-way flap.

Planning notes
 The package includes the two-part chimney with the dimensions from 582 mm to 884 mm. Individual planning solutions can be implemented using the special accessory chimney extension AD 200 322 or by shortening the lower edge of the inner chimney. Clearance above gas appliances min. 65 cm (more than total load gas 12 kW min. 70 cm). Clearance above electric appliances min. 55 cm.
 The air recirculation module with activated charcoal filter can be installed on the external chimney or inner chimney.
 When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the power supply line of the ventilation appliance needs a suitable safety switch.

Connection
 Total connected load 275 W.

Characteristics
Product name/family
Color chimney
Typology
 Chimney
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
 130
Required niche size for installation (HxWxD)
Height of the chimney (mm)
 582-884
Height of product, without chimney (mm)
 70
Net weight (kg)
 22.063
Type of control
 Electronic
Number of speed settings
Maximum output air extraction (m3/h)
 610
Boost position output recirculating (m3/h)
 530.0
Maximum output recirculating air (m3/h)
Boost position air extraction (m³/h)
 810
Number of lights
 3
Noise level (dB(A) re 1 pW)
 66
Diameter of air outlet (mm)
 120 / 150
Grease filter material
 Washable stainless steel
Odour filter
 No
Operating Mode
 Convertible
Delay Shut off modes
Required accessories
Optional accessories
 AA200110, AA200812
Type of lamps used
 LED
Total power of the lamps (W)
 15
Grease filter type
 Multilayer
Clean filter reminders

Consumption and connection features
Connection Rating (W)
 275
Current (A)
 10
Voltage (V)
 220-240
Frequency (Hz)
 60; 50
Plug type
 Gardy plug w/ earthing
Installation typology
 Wall-mounted
Universal Product Code
 825225913887
Material body
 Stainless steel
Approval certificates
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length of electrical supply cord (in)
Plug type
 Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in)
 / x x
Dimensions of the packed product (in)
 23.03 x 25.59 x 38.18
Height of the chimney (in)
Vertical rise height
Required distance above cooktop/ranges
Net weight (lbs)
 49
Gross weight (lbs)
 61

Connecting cable 1.3 m with plug.

Consumption data
 Energy consumption 38.8 kwh/year.
 Ventilation efficiency class A.
 Illumination efficiency class A.
 Grease filter efficiency class B.
 Sound level min. 44 dB / max. 66 dB normal mode.
 Illuminance 731 lx.
 Lamp output 3 x LED 6medium power 5W stripe.
 Dimmable, neutral white LED light for ideal illumination of the whole cooktop
 Neutral white LED light (3600 K), continuously dimmable.
 Energy efficiency class A at a range of energy efficiency classes from A++ to E.

Color Variants
AW240190
 Stainless steel with stainless steel control panel
 Width 90 cm

Optional accessories
AA200110
 Active charcoal filter for retrofitting recirculation module AA 200 812/816
AA200812
 Recirculation module with activated charcoal filter

Installation Accessories
AD200322
 Stainless steel chimney extension
 Length: 1000 mm
AD200392
 Ceiling collar for air ducts
 Stainless steel