



**BO420101**  
**Oven 400 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**Right-hinged**  
**Controls at the top**

**Handleless door / automatic door opening**  
**Pyrolytic system**  
**9 heating methods, with baking stone function**  
**TFT touch display**  
**Panel-free appliance with surface control module**  
**Electronic temperature control from 50 °C to 300 °C**  
**Net volume 76 litres**

#### Heating methods

Hot air.  
 Eco hot air.  
 Top + bottom heat.  
 Top heat.  
 Bottom heat.  
 Hot air + bottom heat.  
 Full surface grill + circulated air.  
 Full surface grill.  
 Baking stone function.

#### Handling

Automatic door opening.  
 Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes.  
 Information key with use indicators.  
 Side-opening door opens up to 180° angle.

#### Features

Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with quadruple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
 Gaggenau enamel.  
 Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
 The door panel surface of the appliance extends 47 mm from the furniture cavity.  
 If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.  
 Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 90° door opening angle.  
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.  
 The mains socket needs to be planned outside of the built-in niche.

#### Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.  
 Total connected load 3.7 kW.

#### Characteristics

**Color / Material Front**  
**Built-in / Free-standing**  
 Built-in  
**Integrated Cleaning system**  
 Pyrolytic  
**Required niche size for installation (HxWxD)**  
 590-590 x 560-560 x 550  
**Dimensions of the product (mm)**  
 595 x 590 x 547  
**Dimensions of the packed product (HxWxD) (mm)**  
 760 x 730 x 660  
**Control Panel Material**  
**Door Material**  
 Glass  
**Net weight (kg)**  
 54.457  
**Usable volume of cavity (l)**  
 76  
**Cooking method**  
 Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat  
**First cavity material**  
**Number of interior lights**  
 1  
**Approval certificates**  
 CE, Eurasian, G-Mark, Ukraine, VDE  
**Length electrical supply cord (cm)**  
**Interior Lights - cavity 1**  
 1  
**Pull-out system**  
 Accessory  
**Clock function**  
 Alarm, Off, On, timer  
**Included accessories**  
 1 x enamel baking tray, suit. pyrolytic clean, 1 x glass pan, 1 x grill shelf  
**Bake Element Wattages cavity 1 (W)**  
**Broil Element Wattages cavity 1 (W)**  
 3000  
**Convection Element Wattages cavity 1 (W)**  
 2100  
**Microwave wattage cavity 1 (W)**  
**Drawer wattage (W)**  
  
**Consumption and connection features**  
**Energy efficiency class (2010/30/EC)**  
 A  
**Energy consumption per cycle conventional (2010/30/EC)**  
 1.25  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
 0.83  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
**Energy efficiency index (2010/30/EC)**  
 95.4  
**Connection Rating (W)**  
 3700  
**Current (A)**  
 16  
**Voltage (V)**  
 220-240  
**Frequency (Hz)**  
 50  
**Plug type**  
 no plug  
**Connecting cable type**  
**Universal Product Code**  
**Color / Material Front**  
**Alternative colors available**  
 BO420111  
**Energy input**  
 Electric  
**Approval certificates**  
 CE, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (in)**  
**Required cutout/niche size for installation (in)**  
 x x  
**Dimensions of the packed product (in)**  
 29.92 x 25.98 x 28.74  
**Net weight (lbs)**

Plan a connection cable.

#### Color Variants

**BO420101**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

#### Included accessories


1 x enamel baking tray, suit. pyrolytic clean.  
 1 x glass pan.  
 1 x grill shelf.

#### Optional accessories


**BA056133**  
**Baking stone**  
**BS020002**  
**Pizza paddle, set of 2**

**GAGGENAU**



BO420101  
 Oven 400 series  
 Full glass door in Gaggenau Anthracite  
 Width 60 cm  
 Right-hinged  
 Controls at the top  
 2020-07-13  
 Page 2



When installed next to each other



Cross section of the top/bottom door edge gaps



\*200 mm in conjunction with BA 016