

Color Variants BO421101 Full glass door in Gaggenau Anthracite Width 60 cm

Included accessories

1 x enamel baking trav. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf.

Optional accessories BA056133 Baking stone BS020002 Pizza paddle, set of 2

Product Variants BO420101 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm **Right-hinged** Controls at the top

BO421101 Oven 400 series Full glass door in Gaggenau Anthracite Width 60 cm Left-hinged Controls at the top

Handleless door / automatic door opening Pyrolytic system 9 heating methods, with baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 50 °C to 300 °C Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

Handling

Automatic door opening. Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 180° angle.

Features

Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Pyrolytic system. Gaggenau enamel. Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible. The door panel surface of the appliance extends 47 mm from the furniture cavity. If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the

furniture cavity. Consider the overhand, incl. the door handle where applicable, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to

Total connected load 3.7 kW.

Characteristics Color / Material Front Built-in / Free-standing Built-in Integrated Cleaning system Pyrolytic Required niche size for installation (HxWxD) 590-590 x 560-560 x 550 Dimensions of the product (mm) 595 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 780 x 760 x 680 **Control Panel Material** Door Material Glass Net weight (kg) 54.557 Usable volume of cavity (I)

Cooking method Baking stone function, Bottom heat, Conventional heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top heat

First cavity material Number of interior lights

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE Length electrical supply cord (cm) Interior Lights - cavity 1

Pull-out system

Accessory **Clock function** Alarm, Off, On, timer Included accessories 1 x enamel baking tray,suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W) 3000 Convection Element Wattages cavity 1 (W)

2100 Microwave wattage cavity 1 (W) Drawer wattage (W)

Consumption and connection features Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.25 Energy consumption gas oven per cycle conventional (2010/30/EC) Energy consumption per cycle forced air convection (2010/30/EC) 0.83 Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC) 95.4 Connection Rating (W) 3700 Current (A) Voltage (V) 220-240 Frequency (Hz) Plug type no plug Connecting cable type Universal Product Code Color / Material Front Alternative colors available BO421111 Energy input Electric Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (in) Required cutout/niche size for installation (in)

Dimensions of the packed product (in) 30.70 x 26.77 x 29.92 Net weight (lbs)



16

50





