

Color Variants BOP241101 Full glass door in Gaggenau Anthracite Width 60 cm BOP241111 Full glass door in Gaggenau Metallic Width 60 cm BOP241131 Full glass door in Gaggenau Silver Width 60 cm

Included accessories

1 x enamel baking tray. suit. pyrolitic clean. 1 x glass pan. 1 x grill shelf. 1 x pluggable meat probe.

Optional accessories BA056133 Baking stone BS020002 Pizza paddle, set of 2 BOP241101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm

Flush installation 13 heating methods, with core temperature probe and baking stone function TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 300 °C Net volume 76 litres

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

Handling

Rotary knob and TFT touch display operation. Clear text display. Option to save individual recipes (incl. core temperature probe). Information key with use indicators. Side-opening door opens up to 110° angle.

Features

Core temperature probe with automatic shut-off. Baking stone socket. Actual temperature display. Rapid heating. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. 60 W halogen light on the top. Chromium-plated side shelf supports with 4 tray levels.

Safety

Thermally insulated door with triple glazing. Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Back wall and ceiling with catalytic coating. Gaggenau enamel. Heated catalyser to clean the oven air. Grease filter in front of hot air fan. Planning notes Door hinge not reversible. The door panel surface of the appliance extends 21 mm from the

furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account. To achieve the 550 mm installation depth, the connection cable needs to

depth, the connection cable needs to follow the slanted edge on the corner of the housing. Characteristics Color / Material Front Built-in / Free-standing Built-in Integrated Cleaning system No Required niche size for installation (HxWxD) 590-590 x 560-560 x 550 Dimensions of the product (mm) 595 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 780 x 760 x 680 Control Panel Material Door Material Glass Net weight (kg) 51.954 Usable volume of cavity (I)

Cooking method

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat First cavity material Number of interior lights

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE Length electrical supply cord (cm) Interior Lights - cavity 1

Pull-out system

Accessory Clock function Alarm, Off, On, timer Included accessories 1 x enamel baking tray,suit. pyrolitic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe

Bake Element Wattages cavity 1 (W) Broil Element Wattages cavity 1 (W) 3000

Convection Element Wattages cavity 1 (W) 2100

Microwave wattage cavity 1 (W) Drawer wattage (W)

Consumption and connection features Energy efficiency class (2010/30/EC)

Energy consumption per cycle conventional (2010/30/EC) 1.25

Energy consumption gas oven per cycle conventional (2010/30/EC)

Energy consumption per cycle forced air convection (2010/30/EC) 0.83

Energy consumption gas oven per cycle forced air convection (2010/30/EC) Energy efficiency index (2010/30/EC) 95.4

Connection Rating (W) 3700

Current (A)

Voltage (V)

220-240 Frequency (Hz)

60; 50 Plug type

fixed connection, no plug Connecting cable type

Universal Product Code 825225914655

Color / Material Front Alternative colors available

BOP241111, BOP241131

Energy input Electric Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (in) Required cutout/niche size for installation (in)

The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 KW. Plan a connection cable.



BOP241101 Oven 200 series Full glass door in Gaggenau Anthracite Width 60 cm 2020-07-31 Page 2



