



**BOP250101**  
**Oven 200 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

**Flush installation**  
**Pyrolytic system**  
**13 heating methods, with core temperature probe and baking stone function**  
**TFT touch display**  
**Panel-free appliance with surface control module**  
**Electronic temperature control from 30 °C to 300 °C**  
**Net volume 76 litres**

#### Heating methods

Hot air. Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting.

#### Handling

Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes (incl. core temperature probe).  
 Information key with use indicators.  
 Side-opening door opens up to 110° angle.

#### Features

Core temperature probe with automatic shut-off.  
 Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

#### Safety

Thermally insulated door with quintuple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
 Gaggenau enamel.  
 Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
 The door panel surface of the appliance extends 21 mm from the furniture cavity.  
 The outer edge of the door handle extends 72 mm from the furniture cavity.  
 Necessary lateral gap between appliance door and furniture panel of min. 5 mm.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 110° door opening angle.  
 For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.  
 To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.  
 The mains socket needs to be planned outside of the built-in niche.

#### Characteristics

**Color / Material Front**  
**Built-in / Free-standing**  
**Built-in**  
**Integrated Cleaning system**  
 Pyrolytic  
**Required niche size for installation (HxWxD)**  
 590-590 x 560-560 x 550  
**Dimensions of the product (mm)**  
 595 x 590 x 547  
**Dimensions of the packed product (HxWxD) (mm)**  
 780 x 760 x 680  
**Control Panel Material**  
**Door Material**  
 Glass  
**Net weight (kg)**  
 54.149  
**Usable volume of cavity (l)**  
 76  
**Cooking method**  
 Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat  
**First cavity material**  
**Number of interior lights**  
 1  
**Approval certificates**  
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
**Length electrical supply cord (cm)**  
**Interior Lights - cavity 1**  
 1  
**Pull-out system**  
 Accessory  
**Clock function**  
 Alarm, Off, On, timer  
**Included accessories**  
 1 x enamel baking tray, suit. pyrolytic clean, 1 x glass pan, 1 x grill shelf, 1 x pluggable meat probe  
**Bake Element Wattages cavity 1 (W)**  
**Broil Element Wattages cavity 1 (W)**  
 3000  
**Convection Element Wattages cavity 1 (W)**  
 2100  
**Microwave wattage cavity 1 (W)**  
**Drawer wattage (W)**  
  
**Consumption and connection features**  
**Energy efficiency class (2010/30/EC)**  
 A  
**Energy consumption per cycle conventional (2010/30/EC)**  
 1.25  
**Energy consumption gas oven per cycle conventional (2010/30/EC)**  
 0.83  
**Energy consumption per cycle forced air convection (2010/30/EC)**  
 0.83  
**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**  
 0.83  
**Energy efficiency index (2010/30/EC)**  
 95.4  
**Connection Rating (W)**  
 3700  
**Current (A)**  
 16  
**Voltage (V)**  
 220-240  
**Frequency (Hz)**  
 50  
**Plug type**  
 fixed connection, no plug  
**Connecting cable type**  
**Universal Product Code**  
 825225914716  
**Color / Material Front**  
**Alternative colors available**  
 BOP250111, BOP250131  
**Energy input**  
 Electric  
**Approval certificates**  
 Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE  
**Length of electrical supply cord (in)**  
**Required cutout/niche size for installation (in)**

## Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 3.7 KW.  
 Plan a connection cable.

#### Color Variants

**BOP250101**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**  
**BOP250111**  
**Full glass door in Gaggenau Metallic**  
**Width 60 cm**  
**BOP250131**  
**Full glass door in Gaggenau Silver**  
**Width 60 cm**

#### Included accessories

1 x enamel baking tray.  
 suit. pyrolytic clean.  
 1 x glass pan.  
 1 x grill shelf.  
 1 x pluggable meat probe.

#### Optional accessories

**BA056133**  
**Baking stone**  
**BS020002**  
**Pizza paddle, set of 2**

#### Product Variants

**BOP251101**  
**Oven 200 series**  
**Full glass door in Gaggenau Anthracite**  
**Width 60 cm**

# GAGGENAU

