

Color Variants

Full glass door in Gaggenau Metallic

1 x STS tray-GN2/3-punched-40 mm

1 x STS tray-GN2/3-unpunched-40 mm

Gastronorm insert, stainless steel, GN

Gastronorm insert, stainless steel, GN

BSP220110

Width 60 cm

deep.

1 x grid.

GN114130

GN114230

2/3

Included accessories

Optional accessories

Steam oven 200 Series Full glass door in Gaggenau Metallic Width 60 cm

Controls at the top

BSP220110

Flush installation Water tank Steaming without pressure with 100% humidity from 30 °C to 100 °C TFT touch display Panel-free appliance with surface control module Electronic temperature control from 30 °C to 100 °C

Heating methods

100 % humidity. Slow steaming. Dough proofing. Defrosting. Regenerating Low temperature steaming.

Handling

Rotary knob and TFT touch display operation. Information key with use indicators.

Side-opening door opens up to 110° angle.

Features

Removable 1.3 litre water tank. Water level warning. Actual temperature display. Timer functions: cooking time, cooking time end, timer, stopwatch. Electronic boiling point detection. 48 W halogen light on the side. Hygienic stainless steel cooking interior. 4 tray levels.

Safety

Child lock Safety shut-off. Cooled housing with temperature protection.

Cleaning

Cleaning aid.
Descaling programme.

Planning notes

Door hinge not reversible. No other electrical appliances should be installed above the BSP. The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture cavity.

Necessary lateral gap between appliance door and furniture panel of min. 5 mm.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner

of the housing.
The mains socket needs to be planned outside of the built-in niche.

Total connected load 1.9 KW. Connection cable 1.5 m without plug. Characteristics

Color / Material Front

Built-in / Free-standing

Built-in

Door opening Lateral

Required niche size for installation (HxWxD)

Dimensions

Dimensions of the packed product

(HxWxD) 575 x 660 x 690

Control Panel Material

Door Material Glass

Net weight

34.158

Approval certificates

VDE

Length electrical supply cord

Connection Rating

1900

Fuse protection

Voltage

220-240

Frequency

50; 60

Plug type

fixed connection, no plug

Connecting cable type

Approval certificates

, VDE

Consumption and connection features

2021-09-13 Page 1



BSP220110 Steam oven 200 Series Full glass door in Gaggenau Metallic Width 60 cm Controls at the top

2021-09-13 Page 2





