

Color Variants

Full glass door in Gaggenau Silver

Full glass door in Gaggenau Metallic

1 x STS tray-GN2/3-punched-40 mm

1 x STS tray-GN2/3-unpunched-40 mm

Gastronorm insert, stainless steel, GN

Gastronorm insert, stainless steel, GN

BSP250130

Width 60 cm

BSP250110

Width 60 cm

deep

deep.

1 x grid.

GN114130

GN114230

Product Variants BSP251130

Width 60 cm

Controls at the top

Combi-steam oven 200 series Full glass door in Gaggenau Silver

1/3

2/3

Included accessories

1 x pluggable meat probe.

Optional accessories

BSP250130

Combi-steam oven 200 series

Full glass door in Gaggenau Silver

Width 60 cm

Controls at the top

Flush installation

Water tank

Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%

TFT touch display

Panel-free appliance with surface control module

Steaming without pressure

Electronic temperature control from 30 °C to 230 °C

Core temperature probe, removable

Heating methods

Hot air + 100 % humidity.

Hot air + 80 % humidity.

Hot air + 60 % humidity.

Hot air + 30 % humidity.

Hot air + 0 % humidity.

Dough proofing.

Defrosting.

Regenerating.

Low temperature cooking.

Handling

Rotary knob and TFT touch display operation.

Option to save individual recipes (incl. core temperature probe). Information key with use indicators.

Side-opening door opens up to 110° angle.

Features

Removable 1.3 litre water tank. Water level warning.

Core temperature probe with automatic shut-off.

Actual temperature display. Timer functions: cooking time, cooking

time end, timer, stopwatch, long-term

Electronic boiling point detection. 48 W halogen light on the side. Hygienic stainless steel cooking

4 tray levels.

Safety

Child lock

Safety shut-off.

Cooled housing with temperature

Cleaning

Cleaning aid.

Drying programme.

Descaling programme.

Grease filter, dishwasher-safe.

Planning notes

angle.

Door hinge not reversible. No other electrical appliances should be installed above the BS.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

The outer edge of the door handle extends 72 mm from the furniture

cavity. Necessary lateral gap between appliance door and furniture panel of

min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers

next to the appliance. When planning a corner solution, pay attention to the 110° door opening

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside of the built-in niche.

Characteristics

Color / Material Front

Built-in / Free-standing

Built-in

Door opening Lateral

Required niche size for installation (HxWxD)

Connection

Total connected load 1.9 KW.

Connection cable 1.5 m without plug.

Dimensions

455 x 590 x 547

Dimensions of the packed product (HxWxD) (mm)

575 x 660 x 690

Control Panel Material

Door Material

Net weight (kg)

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length electrical supply cord (cm)

Cooking method

Defrost, fermentation, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, low temperature steam, Regeneration

Time-setting Options

Electrical connection rating (W)

Current (A)

Voltage (V)

Frequency (Hz) 50; 60

Plug type

fixed connection, no plug

Connecting cable type

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Universal Product Code

825225915010 Color / Material Front

Alternative colors available

BSP250100, BSP250110

Energy input Electric

Current (A)

Voltage (V)

Frequency (Hz)

Approval certificates

CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (in)

Plug type

fixed connection, no plug

Appliance Dimensions (h x w x d) (in)

Required cutout/niche size for installation (in)

Dimensions of the packed product (in)

Net weight (lbs)

79.000

Gross weight (lbs)

Consumption and connection features

2021-02-22

Page 1



BSP250130
Combi-steam oven 200 series
Full glass door in Gaggenau Silver
Width 60 cm
Controls at the top

2021-02-22 Page 2





