



BSP251100
Combi-steam oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Left-hinged
Controls at the top

Flush installation
Water tank
Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
TFT touch display
Panel-free appliance with surface control module
Steaming without pressure
Electronic temperature control from 30 °C to 230 °C
Core temperature probe, removable

Heating methods
Hot air + 100 % humidity.
Hot air + 80 % humidity.
Hot air + 60 % humidity.
Hot air + 30 % humidity.
Hot air + 0 % humidity.
Dough proofing.
Defrosting.
Regenerating.
Low temperature cooking.

Handling
Rotary knob and TFT touch display operation.
Option to save individual recipes (incl. core temperature probe).
Information key with use indicators.
Side-opening door opens up to 110° angle.

Features
Removable 1.3 litre water tank.
Water level warning.
Core temperature probe with automatic shut-off.
Actual temperature display.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
Electronic boiling point detection.
48 W halogen light on the side.
Hygienic stainless steel cooking interior.
4 tray levels.

Safety
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning
Cleaning aid.
Drying programme.
Descaling programme.
Grease filter, dishwasher-safe.

Planning notes
Door hinge not reversible.
No other electrical appliances should be installed above the BS.
The door panel surface of the appliance extends 21 mm from the furniture cavity.
The outer edge of the door handle extends 72 mm from the furniture cavity.
Necessary lateral gap between appliance door and furniture panel of min. 5 mm.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 110° door opening angle.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Characteristics
Color / Material Front
Built-in / Free-standing
Built-in
Door opening
Lateral
Required niche size for installation (HxWxD)
Dimensions of the product (mm)
455 x 590 x 547
Dimensions of the packed product (HxWxD) (mm)
575 x 660 x 690
Control Panel Material
Door Material
Glass
Net weight (kg)
36.008
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE
Length electrical supply cord (cm)
150
Cooking method
Defrost, fermentation, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, low temperature steam, Regeneration
Time-setting Options

Consumption and connection features
Electrical connection rating (W)

Current (A)
8
Voltage (V)
220-240

Frequency (Hz)
50; 60

Plug type
fixed connection, no plug

Connecting cable type
Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Universal Product Code
825225915027

Color / Material Front
Alternative colors available
BSP251110, BSP251130

Energy input
Electric

Current (A)
8

Voltage (V)
220-240

Frequency (Hz)
50; 60

Approval certificates
Australia Standards, CE, Eurasian, G-Mark, Ukraine, VDE

Length of electrical supply cord (in)

Plug type
fixed connection, no plug

Appliance Dimensions (h x w x d) (in)
Required cutout/niche size for installation (in)

Dimensions of the packed product (in)

Net weight (lbs)
79.000

Gross weight (lbs)
84

2020-03-06
Page 1

Connection

Total connected load 2.0 kW.
Connection cable 1.5 m without plug.

Color Variants

BSP251100
Full glass door in Gaggenau Anthracite
Width 60 cm
BSP251110
Full glass door in Gaggenau Metallic
Width 60 cm
BSP251130
Full glass door in Gaggenau Silver
Width 60 cm

Included accessories

1 x STS tray-GN2/3-punched-40 mm deep.
1 x STS tray-GN2/3-unpunched-40 mm deep.
1 x grid.
1 x pluggable meat probe.

Optional accessories

GN114130
Gastronorm insert, stainless steel, GN 1/3
GN114230
Gastronorm insert, stainless steel, GN 2/3
GN410130
Gastronorm lid, stainless steel, GN 1/3
GN410230
Gastronorm lid, stainless steel, GN 2/3

Product Variants

BSP250100
Combi-steam oven 200 series
Full glass door in Gaggenau Anthracite
Width 60 cm
Right-hinged
Controls at the top