

Color Variants BSP251130 Full glass door in Gaggenau Silver Width 60 cm BSP251110 Full glass door in Gaggenau Metallic Width 60 cm

Included accessories

1 x STS tray-GN2/3-punched-40 mm deep. 1 x STS tray-GN2/3-unpunched-40 mm deep. 1 x grid. 1 x pluggable meat probe.

Optional accessories

GN114130 Gastronorm insert, stainless steel, GN 1/3 GN114230 Gastronorm insert, stainless steel, GN 2/3

Product Variants BSP250130 Combi-steam oven 200 series Full glass door in Gaggenau Silver Width 60 cm Controls at the top

BSP251130

Combi-steam oven 200 series Full glass door in Gaggenau Silver Width 60 cm Controls at the top

Flush installation Water tank Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100% TFT touch display Panel-free appliance with surface control module Steaming without pressure Electronic temperature control from 30 °C to 230 °C Core temperature probe, removable

Heating methods

Hot air + 100 % humidity. Hot air + 80 % humidity. Hot air + 60 % humidity. Hot air + 30 % humidity. Hot air + 0 % humidity. Dough proofing. Defrosting. Regenerating. Low temperature cooking.

Handling

Rotary knob and TFT touch display operation. Option to save individual recipes (incl. core temperature probe). Information key with use indicators. Side-opening door opens up to 110° angle.

Features

Removable 1.3 litre water tank. Water level warning. Core temperature probe with automatic shut-off. Actual temperature display. Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer. Electronic boiling point detection. 48 W halogen light on the side. Hygienic stainless steel cooking interior.

4 tray levels.

Safety

Child lock. Safety shut-off. Cooled housing with temperature protection.

Cleaning

Cleaning aid. Drying programme. Descaling programme. Grease filter, dishwasher-safe.

Planning notes

Door hinge not reversible. No other electrical appliances should be installed above the BS. The door panel surface of the appliance extends 21 mm from the furniture cavity. The outer edge of the door handle extends 72 mm from the furniture cavity. Necessary lateral gap between appliance door and furniture panel of min. 5 mm. Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance. When planning a corner solution, pay attention to the 110° door opening angle. To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing. The mains socket needs to be planned outside of the built-in niche.

Color / Material Front Built-in / Free-standing Built-in

Characteristics

Door opening Lateral Required niche size for installation (HxWxD) Dimensions 455 x 590 x 547 Dimensions of the packed product (HxWxD) (mm) 575 x 660 x 690 **Control Panel Material** Door Material Glas Net weight (kg) 36.158 Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE Length electrical supply cord (cm) Cooking method Defrost, fermentation, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot

steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, low temperature steam, Regeneration Time-setting Options

Electrical connection rating (W) Current (A)

Voltage (V)

220-240 Frequency (Hz)

50; 60

Plug type fixed connection, no plug Connecting cable type Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE

Universal Product Code 825225915034

Color / Material Front Alternative colors available

BSP251100, BSP251110

Energy input Electric Current (A)

8 Voltage (V)

220-240 Frequency (Hz) 50; 60 Approval certificates CE, Eurasian, G-Mark, Ukraine, VDE Length of electrical supply cord (in) Plug type fixed connection, no plug Appliance Dimensions (h x w x d) (in) Required cutout/niche size for installation (in) Dimensions of the packed product (in) Net weight (Ibs) 80.000

Gross weight (lbs) 85.000

Consumption and connection features 2021-02-22 Page 1



Total connected load 1.9 KW. Connection cable 1.5 m without plug.



BSP251130 Combi-steam oven 200 series Full glass door in Gaggenau Silver Width 60 cm Controls at the top

2021-02-22 Page 2





