



Color Variants

BX480111
Stainless steel-backed full glass door
Width 76 cm

Included accessories

2 x enamel baking tray, suit. pyrolytic clean.
1 x rotary spit.
2 x grill shelf.
2 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA058133
Baking stone
BS020002
Pizza paddle, set of 2

Product Variants

BX481111
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

BX480111
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered

Pyrolytic system
17 heating methods, with core temperature probe, rotisserie spit and baking stone function
TFT touch display
Electronic temperature control from 30 °C to 300 °C
2 x 110 litres net volume

Heating methods

Hot air. Eco hot air. Top + bottom heat. Top + 1/3 bottom heat. Top heat. 1/3 top + bottom heat. Bottom heat. Hot air + bottom heat. Hot air + 1/3 bottom heat. Full surface grill + circulated air. Full surface grill. Compact grill. Baking stone function. Roaster function. Dough proofing. Defrosting. Keeping warm.

Handling

Rotary knob and TFT touch display operation.
Clear text display.
Information key with use indicators.
Side-opening door opens up to 180° angle.

Features

Core temperature probe with automatic shut-off (lower oven).
Rotisserie spit (lower oven).
Baking stone socket.
Actual temperature display.
Rapid heating.
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
60 W halogen light on the top.
10 W halogen light on the side.
Enamelled side shelf supports with 5 tray levels, pyrolysis-safe.

Safety

Thermally insulated door with quadruple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic system.
Gaggenau enamel.
Heated catalyser to clean the oven air.

Planning notes

Door hinge not reversible.
The door panel surface of the appliance extends 47 mm from the furniture cavity.
The outer edge of the door handle extends 94 mm from the furniture cavity.
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the 90° door opening angle.
To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.
The mains socket needs to be planned outside of the built-in niche.

Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.
Total connected load 9.2 KW.
Plan a connection cable.

Characteristics

Color / Material Front
Built-in / Free-standing
Built-in
Integrated Cleaning system
Dimensions of the product (mm)
1428 x 752 x 547
Dimensions of the packed product (HxWxD) (mm)
1765 x 755 x 840
Control Panel Material
Alu
Door Material
Glass
Net weight (kg)
162.010
Usable volume of cavity (l)
110
Cooking method
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming
First cavity material
Enameled
Number of interior lights
2
Approval certificates
Australia Standards, CE, Ukraine, VDE
Length electrical supply cord (cm)
Cooking method second cavity
Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming
Timer
Yes
Included accessories cavity 1
2 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 2 x grill shelf, 2 x grill tub with grid, 1 x pluggable meat probe
Bake Element Wattages cavity 1 (W)
Broil Element Wattages cavity 1 (W)
3900
Convection Element Wattages cavity 1 (W)
Microwave wattage cavity 1 (W)

Consumption and connection features
Energy efficiency class (2010/30/EC)
A
Energy consumption per cycle conventional (2010/30/EC)
1.53
Energy consumption gas oven per cycle conventional (2010/30/EC)
Energy consumption per cycle forced air convection (2010/30/EC)
0.96
Energy consumption gas oven per cycle forced air convection (2010/30/EC)
Energy efficiency index (2010/30/EC)
95.0
Connection Rating (W)
9200
Current (A)
Voltage (V)
220-240
Frequency (Hz)
50
Plug type
fixed connection, no plug
Connecting cable type
Universal Product Code
825225915058
Color / Material Front
Alternative colors available
Energy input
Electric
Approval certificates
Australia Standards, CE, Ukraine, VDE
Length of electrical supply cord (in)
Required cutout/niche size for installation (in)

GAGGENAU

BX480111
Double oven 400 series
Stainless steel-backed full glass door
Width 76 cm
Controls centered
2020-07-02
Page 2

