



**EB333110**

**Oven**

**stainless steel**

**Width 90 cm**

**One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel**  
**Cushioned door opening and closing system**  
**Diagonally positioned light sources for optimal interior lighting**  
**Pyrolytic system**  
**17 heating methods, with core temperature probe, rotisserie spit and baking stone function**  
**Hot air fan rotates in both directions for ideal heat distribution**  
**TFT touch display**  
**Panel-free appliance with control module behind glass**  
**Electronic temperature control from 50 °C to 300 °C**  
**Net volume 83 litres**

**Heating methods**

Hot air.  
Eco hot air.  
Top + bottom heat.  
Top + 1/3 bottom heat.  
Top heat.  
1/3 top + bottom heat.  
Bottom heat.  
Hot air + bottom heat.  
Hot air + 1/3 bottom heat.  
Full surface grill + circulated air.  
Full surface grill.  
Compact grill.  
Baking stone function.  
Roaster function.  
Dough proofing.  
Defrosting.  
Keeping warm.

**Handling**

Rotary knob and TFT touch display operation.  
Clear text display.  
Option to save individual recipes (incl. core temperature probe).  
Information key with use indicators.  
Front-hinged door with 90° door opening angle.

**Features**

Core temperature probe with automatic shut-off.  
Rotisserie spit.  
Baking stone socket.  
Actual temperature display.  
Rapid heating.  
Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.  
60 W halogen light on the top.  
2 x 10 W halogen light on the side.  
Enamelled side shelf supports with 3 tray levels, pyrolysis-safe.

**Safety**

Thermally insulated door with quintuple glazing.  
Child lock.  
Safety shut-off.  
Cooled housing with temperature protection.

**Cleaning**

Pyrolytic system.  
Gaggenau enamel.  
Heated catalyser to clean the oven air.

**Planning notes**

The door panel surface of the appliance extends 40 mm from the furniture cavity.

**Characteristics**

**Color / Material Front**

**Built-in / Free-standing**

**Built-in**

**Integrated Cleaning system**

Pyrolytic

**Required niche size for installation (HxWxD)**

475-475 x 860-860 x 560

**Dimensions of the product (mm)**

480 x 890 x 550

**Dimensions of the packed product (HxWxD) (mm)**

710 x 720 x 990

**Control Panel Material**

Stainless steel

**Door Material**

Stainless steel behind glass

**Net weight (kg)**

82.197

**Usable volume of cavity (l)**

83

**Cooking method**

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, Roaster function, Top heat, warming

**First cavity material**

**Number of interior lights**

3

**Approval certificates**

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark, Ukraine, VDE

**Length electrical supply cord (cm)**

**Interior Lights - cavity 1**

3

**Pull-out system**

Accessory

**Clock function**

Alarm, Off, On, timer

**Included accessories**

1 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

**Bake Element Wattages cavity 1 (W)**

**Broil Element Wattages cavity 1 (W)**

3900

**Convection Element Wattages cavity 1 (W)**

1900

**Microwave wattage cavity 1 (W)**

**Drawer wattage (W)**

**Consumption and connection features**

**Energy efficiency class (2010/30/EC)**

A

**Energy consumption per cycle conventional (2010/30/EC)**

1.32

**Energy consumption gas oven per cycle conventional (2010/30/EC)**

0.86

**Energy consumption per cycle forced air convection (2010/30/EC)**

0.86

**Energy consumption gas oven per cycle forced air convection (2010/30/EC)**

95.6

**Energy efficiency index (2010/30/EC)**

95.6

**Connection Rating (W)**

5380

**Current (A)**

25

**Voltage (V)**

220-240

**Frequency (Hz)**

50

**Plug type**

fixed connection, no plug

**Connecting cable type**

**Universal Product Code**

825225931737

**Color / Material Front**

**Alternative colors available**

**Energy input**

Electric

**Approval certificates**

Australia Standards, CCC, CE, China, China ROHS 20, Eurasian, G-Mark,

The outer edge of the door handle extends 90 mm from the furniture cavity.

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 15 mm. The planning notes for the cooktops (particularly regarding ventilation, gas/electric connection) must be taken into account.

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The mains socket needs to be planned outside the built-in niche.

**Connection**

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.

Total connected load 5.4 kW.

Plan a connection cable.

**Color Variants**

EB333110

stainless steel

Width 90 cm

**Included accessories**

1 x enamel baking tray.  
suit. pyrolytic clean.  
1 x rotary spit.  
1 x grill shelf.  
1 x grill tub with grid.  
1 x pluggable meat probe.

**Optional accessories**

BA058133

Baking stone

BS020002

Pizza paddle, set of 2

**GAGGENAU**